

FSG2SP35

Pressure switch 4,6 bar - G 3/8 femal - 2 entries Pg 13.5

COMMERCIALISED

Main

Electromechanical pressure sensor		
FSG		
G 3/8 (female) conforming to ISO 228		
Fresh water (0-70 °C), sea water (0-70 °C)		
2 entries incorporating Pg 13.5 plastic cable gland, cable outer diameter: 9-13 mm conforming to NF C 68-300		
Contacts type and composition 2 NC snap action		
Not applicable		
Regulation between 2 thresholds		
Screw-clamp terminals, clamping capacity: 1 x 12 x 2 mm²		
Adjustable differential		
Internal		
Without		
Power circuit		

Complementary

Materials in contact with fluid	Zinc plated steel nitrile nylon 6/6
Enclosure material	PS
Operating position	Any position
Pressure actuator	Diaphragm
Terminal block type	4 terminals
Operating rate	10 CYCLE_PER_MINUTE

Environment

Standards	IEC 60730 CE	
Protective treatment	TC	
Electrical shock protection class Class I conforming to IEC 536		
IP degree of protection	IP65 conforming to IEC 60529	

Packing Units

Unit type of package 1	PCE
Number of units in package 1	1
Package 1 height	11.5 CENTIMETER
Package 1 width	7.2 CENTIMETER
Package 1 length	10.6 CENTIMETER
Package 1 weight	340.194 GRAM

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.

This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.

Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Updated: 22/05/2025



