SC380A400

Hyde Park, Ultrasonic sensor, discrete, 12 mm barrel, 12 24 V DC



Main

Range of product	Hyde Park
Sensor type	Ultrasonic sensor
Series name	Superprox +
Device short name	SC380
Sensor design	Cylindrical M12
Type of sensing window	Configurable
Material	Plastic
Enclosure material	ULTEM
Front material	Glass epoxy
Type of output signal	Discrete
ISO thread	M12 x 1
Wiring technique	4-wire
[Us] rated supply voltage	1224 V DC with overload and short-circuit protection
Supply voltage limits	1028 V DC
Electrical connection	Remote male connector M12 4 pins, 152 mm cable length
Product specific application	Discrete proximity

Complementary

101.6 mm
0.7 mm
6.4 mm
500 kHz
0.7 %
8°
Cylinder diameter 2.5 mm - up to 1 mm sensing distance
25 mA
100 mA with reverse polarity protection
12 mm
12 mm
12 mm
53.08 mm
0.011 kg

Environment

Product certifications	UL	
Marking	CE	
NEMA degree of protection	NEMA 4X (indoor use only)	
IP degree of protection	IP67	
Ambient air temperature for operation	-3070 °C	
Ambient air temperature for storage	-40100 °C	
Relative humidity	100 % without condensation	
Vibration resistance	+/-1 mm conforming to IEC 60068-2-6 (f = 1055 Hz)	
Shock resistance	30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27	
Resistance to electromagnetic fields	10 V/m level 3 conforming to IEC 61000-4-3	
Resistance to fast transients	1 kV level 3 conforming to IEC 61000-4-4	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.415 cm
Package 1 Width	3.81 cm
Package 1 Length	8.415 cm
Package 1 Weight	362.874 g

Offer Sustainability

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
sustainability@tesensors.com

Contractual warranty

	•	
Warranty	18 months	
Trainanty	To monate	

