



Type Examination Certificate

No. C5AUK 022629 0056 Rev. 00

Holder of Certificate: **Karl Dungs GmbH & Co. KG**
Karl-Dungs-Platz 1
73660 Urbach
GERMANY

Product: **Fittings (Gas)**
Multifunctional controls

DMV-... 5.../12

The Approved Body of TUV SUD BABT Unlimited confirms according to the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations, UKSI 2018:389 (as amended by UKSI 2019:696), that in the conformity assessment procedure in accordance with Article 14 the listed product has been assessed in a type examination (module B - production type) and complies with the relevant provisions according to Annex I on appliances burning gaseous fuels. It refers only to the sample submitted for testing and certification and on its technical documentation. See also notes overleaf.

Test report no.: V-M 1707-00/22

Valid until: 2032-07-17

Date, 2022-07-19

(Johannes Steiglechner)



Type Examination Certificate

No. C5AUK 022629 0056 Rev. 00

Model(s): DMV 525/12, DMV-D 525/12,
DMV 5065/12, DMV-D 5065/12,
DMV-DLE 5065/12,
DMV 5080/12, DMV-D 5080/12,
DMV-DLE 5080/12,
DMV 5100/12, DMV-D 5100/12,
DMV-DLE 5100/12,
DMV 5125/12, DMV-D 5125/12

Models

nominal size	type designation	rated voltage	rated power (hold / start)
Rp 2 (DN65)	DMV 525/12	AC 110 V, AC 230 V; 50 – 60 Hz	2x 16 W / 2x 65 W
Rp 2 (DN65)	DMV-D 525/12	AC 110 V, AC 230 V; 50 – 60 Hz	2x 15 W / 2x 65 W
DN 65	DMV 5065/12	AC 110 V, AC 230 V; 50 – 60 Hz DC 24 – 28 V	2x 20 W / 2x 95 W 2x 17 W / 2x 95 W
DN 65	DMV-D 5065/12		
DN 65	DMV-DLE 5065/12		
DN 80	DMV 5080/12	AC 230 V; 50 – 60 Hz	2x 25 W / 2x 125 W
DN 80	DMV-D 5080/12	AC 110 V; 50 – 60 Hz	2x 26 W / 2x 125 W
DN 80	DMV-DLE 5080/12	DC 24 – 28 V	2x 20 W / 2x 100 W
DN 100	DMV 5100/12	AC 230 V; 50 – 60 Hz	2x 25 W / 2x 125 W
DN 100	DMV-D 5100/12	AC 110 V; 50 – 60 Hz	2x 26 W / 2x 125 W
DN 100	DMV-DLE 5100/12	DC 24 – 28 V	2x 20 W / 2x 100 W
DN 125	DMV 5125/12	AC 230 V; 50 – 60 Hz	2x 40 W / 2x 250 W
DN 125	DMV-D 5125/12	DC 24 – 28 V	2x 40 W / 2x 270 W



Type Examination Certificate

No. C5AUK 022629 0056 Rev. 00

Technical data / range of application

gas family	all gases of 1 st , 2 nd and 3 rd gas family
valve class according to DIN EN 161	A
group according to DIN EN 161	2
max. operating pressure	500 mbar /50 kPa
ambient temperature	-15°C to +60°C (version with sealing material NBR) 0°C to +60°C (version with sealing material "Viton")
installation position	actuator in vertical to horizontal position

Electrical data

rated voltage	see models
degree of protection	IP54

Tested according to: DIN EN 126:2012
DIN EN 161:2013
DIN EN 13611:2011