Limit switch contact block, Limit switches XC Standard, 1 co, 2 nc sl with gold flashed connector



Main

| Range of product | Telemecanique Limit switches XC Standard |
|-------------------------------|--|
| Series name | Standard format |
| Product or component type | Limit switch contact block |
| Device short name | XE2N |
| Associated body | ZCKS7 ZCKJ7D ZCKL7 ZCKJ7 ZCKJ7 ZCKJ7 ZCP27 ZCKM7 ZCD27 |
| Number of poles | 2 |
| Contacts type and composition | 2 NC |
| Contact operation | Slow-break, simultaneous |

Complementary

| Product compatibility | XCKS XCKM XCKD XCKL XCKJ XCKP |
|--|---|
| Electrical connection | Screw-clamp terminals, clamping capacity: 1 x 0.52 x 2.5 mm ² |
| Contacts insulation form | Zb |
| Contacts material | Gold flashed contacts |
| Positive opening | With |
| Minimum actuation speed | 6 m/min |
| Contact code designation | A300, AC-15 (Ue = 240 V), Ie = 3 A, Ithe = 10 A conforming to EN/IEC 60947-5-1 appendix A Q300, DC-13 (Ue = 250 V), Ie = 0.27 A conforming to EN/IEC 60947-5-1 appendix A |
| Maximum resistance across terminals | 25 mOhm conforming to IEC 60255-7 category 3 |
| [Ui] rated insulation voltage | 300 V conforming to UL 508 500 V (pollution degree 3) conforming to IEC 60947-1 300 V conforming to CSA C22.2 No 14 |
| [Uimp] rated impulse withstand voltage | 6 KV conforming to IEC 60664 6 kV conforming to IEC 60947-1 |
| Short-circuit protection | 10 A cartridge fuse, type gG |
| Electrical durability | 5000000 Cycles, DC-13 120 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 13 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |

Packing Units

| PCE | |
|-----------|----------------------------|
| 1 | |
| 11.000 cm | |
| 2.500 cm | |
| 7.500 cm | |
| | 1 11.000 cm 2.500 cm |

| Package 1 Weight | 21.000 g |
|------------------------------|------------|
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 90 |
| Package 2 Height | 30 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 2.310 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 720 |
| Package 3 Height | 45.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 30.480 kg |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|--|---|
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

