## XS8C4A1MPN12TF

# Inductive proximity sensors XS, inductive sensor rect 40x40x117 24 240 V



#### Main

Range of product	Telemecanique Inductive proximity sensors XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Device application	-
Sensor name	XS8
Sensor design	Form 40 x 40 x 117
Size	40 mm
Body type	Fixed
Detector flush mounting acceptance	Non flush mountable
Material	Plastic
Enclosure material	PBT
Type of output signal	Discrete
Wiring technique	2-wire
[Sn] nominal sensing distance	40 Mm flush mountable 60 mm non flush mountable
Discrete output function	1 NO
Output circuit type	AC/DC
Electrical connection	Cable
Cable length	12 m
Switching capacity in mA	5200 mA DC 5300 mA AC
IP degree of protection	IP68 double insulation conforming to IEC 60529

#### Complementary

Frontal
PBT
2040 Mm flush mountable 2060 mm non flush mountable
115% of Sr
2 x 0.34 mm²
PVC
20264 V AC/DC
1.5 mA open state
<= 150 Hz
<5.5 V (closed)
<= 10 mA no-load
15 ms
0.3 ms
6 ms
CE
40 mm
118 mm
40 mm
0.71 kg

#### **Environment**

Product certifications	CCC[RETURN]CSA[RETURN]UL
Ambient air temperature for operation	-4070 °C
Ambient air temperature for storage	-4085 °C
Vibration resistance	25 gn amplitude = +/- 2 mm (f = 1055 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn for 11 ms conforming to IEC 60068-2-27

## Packing Units

PCE	
1	
14.3 cm	
5.0 cm	
5.0 cm	
237.0 g	
	1 14.3 cm 5.0 cm 5.0 cm

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

### Contractual warranty

warranty	Warranty 18 months	
----------	--------------------	--