XSAV11373TFEX

Rotation monitoring for hazardous area dust, M30, Sn10mm, 6...150c/mn, NC, cable 2 m, -40°C



Main

Range of product	Telemecanique Inductive proximity sensors XS	
Series name	Application	
Sensor type	Inductive proximity sensor	
Device application	Rotation monitoring ATEX dust	
Sensor name	XSA	
Sensor design	Cylindrical M30	
Size	30 mm	
Body type	Fixed	
Detector flush mounting acceptance	Flush mountable	
Material	Metal	
Enclosure material	Nickel plated brass	
[Sn] nominal sensing distance	10 mm	
Type of output signal	Discrete	
Wiring technique	3-wire	
Discrete output function	1 NC	
Output circuit type	DC	
Discrete output type	PNP	
Electrical connection	Cable	
Cable length	2 m	
[Us] rated supply voltage	1248 V DC with reverse polarity protection	
Switching capacity in mA	<= 200 mA with overload and short-circuit protection	
IP degree of protection	IP67 conforming to IEC 60529	

Complementary

Thread type Detection face	M30 x 1.5
Detection face	
Detection lace	Frontal
Front material	PPS
Sensing range	> 815 mm
Adjustable frequency range	6150 cyc/mn
Operating zone	08 mm
Differential travel	315% of Fr
Repeat accuracy	3% of Sr
Cable composition	3 x 0.34 mm ²
Wire insulation material	PVC
Status LED	Output state: 1 LED (red)
Supply voltage limits	1058 V DC
Switching frequency	<= 100 Hz
Maximum voltage drop	<1.8 V (closed state)
Current consumption	015 mA no-load
Run-up delay at power-up	9 s standard
Marking	II2 D-Ex tb IIIC T90°C Db IP67
Threaded length	57 mm
Length	81 mm

Environment

Environmental characteristic	Hazardous location
Standards	EN/IEC 60079-31 EN/IEC 60079-0
Directives	2014/34/EU - ATEX directive
Product certifications	INERIS 04ATEX0022[RETURN]IEC-Ex INE 17.0006
Ambient air temperature for operation	-4060 °C
Dust zone	Zone 21 - 22

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.800 cm
Package 1 Width	19.100 cm
Package 1 Length	19.100 cm
Package 1 Weight	248.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.740 kg
Unit Type of Package 3	P06
Number of Units in Package 3	160
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	51.840 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Circularity Profile	☑ End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

	•	
Warranty		18 months

