



# XUB8APXNM12

Photoelectric sensors XU, Photo electric Sensor, Cylindrical, Plastic, Diffuse BGS, Smax 0.3 m, PNP, Connector M12

COMMERCIALISED

## Main

|                               |                                               |
|-------------------------------|-----------------------------------------------|
| Range of product              | Telemecanique Photoelectric sensors XU        |
| Series name                   | General purpose single mode                   |
| Electronic sensor type        | Photo-electric sensor                         |
| Sensor name                   | XUB                                           |
| Sensor design                 | Cylindrical M18                               |
| Detection system              | Diffuse with background suppression           |
| Material                      | Plastic                                       |
| Line of sight type            | Axial                                         |
| Type of output signal         | Discrete                                      |
| Supply circuit type           | DC                                            |
| Wiring technique              | 4 wires                                       |
| [Sn] nominal sensing distance | 0.3-0.3 m diffuse with background suppression |
| Discrete output type          | PNP                                           |
| Discrete output function      | 1 NO or 1 NC programmable                     |
| Electrical connection         | 1 male connector M12, 4 pins                  |
| Emission                      | Red LED diffuse with background suppression   |

## Complementary

|                           |                                                                        |
|---------------------------|------------------------------------------------------------------------|
| Enclosure material        | PC/PBT                                                                 |
| Lens material             | PMMA                                                                   |
| Output type               | Discrete                                                               |
| Status LED                | 1 LED (green) for supply on/stability, 1 LED (orange) for output state |
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection                          |
| Switching capacity in mA  | <= 100 mA (overload and short-circuit protection)                      |

|                      |                              |
|----------------------|------------------------------|
| Switching frequency  | 1000 Hz                      |
| Maximum voltage drop | <2 V (closed state)no-load   |
| Current consumption  | < 20 mA no load              |
| Delay first up       | 300 MILLISECOND              |
| Delay response       | 0.5 MILLISECOND              |
| Delay recovery       | 0.5 MILLISECOND              |
| Setting-up           | Sensitivity by potentiometer |

## Environment

|                         |                                                                                             |
|-------------------------|---------------------------------------------------------------------------------------------|
| Vibration resistance    | 7 gn, amplitude = +/- 1.5 mm (f = 10-55 Hz)for every axis conforming to IEC 60068-2-6       |
| Shock resistance        | 30 gn (duration = 11 ms) for for every axis conforming to IEC 60068-2-27                    |
| IP degree of protection | IP67 conforming to IEC 60529, IP65 conforming to IEC 60529, IP69K conforming to DIN 40050-9 |

## Packing Units

|                                |                |
|--------------------------------|----------------|
| Unit type of package 1         | PCE            |
| Number of units in package 1 1 |                |
| Package 1 height               | 4.2 CENTIMETER |
| Package 1 width                | 9.6 CENTIMETER |
| Package 1 length               | 6.6 CENTIMETER |
| Package 1 weight               | 60 KILOGRAM    |
| Package 2 height               | 15 CENTIMETER  |
| Package 2 width                | 30 CENTIMETER  |
| Package 2 length               | 40 CENTIMETER  |
| Package 2 weight               | 3.18 KILOGRAM  |
| Indivisible sale quantity      | 1              |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.  
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Updated: 26/08/2025