XUY1169AD6A2

Photoelectric sensors XU, Roller Sensor 1169 mm N6, P162 IP50 Adhesive Cable 2 m, Wires



Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	Application, conveyor system and access control
Electronic sensor type	Photo-electric sensor
Sensor name	XUY
Sensor design	Roller sensor
Detection system	Diffuse
Material	Metal
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	4-wire
Discrete output type	PNP
Discrete output function	1 NO
Electrical connection	Cable
Cable length	2 m
Product specific application	Conveyor system
Emission	Infrared
[Sn] nominal sensing distance	65 mm diffuse

Complementary

Complementary		
Enclosure material	Aluminium	
Lens material	Polycarbonate	
Cover material	PVC	
Pulse frequency	1 kHz	
Output type	Solid state	
Status LED	1 LED color: yellow for output signal	
[Us] rated supply voltage	1224 V DC with reverse polarity protection	
Supply voltage limits	1830 V DC	
Switching capacity in mA	100 mA (overload and short-circuit protection)	
Switching frequency	500 Hz	
Maximum voltage drop	<2 V at 100 mA	
Current consumption	< 35 mA no-load	
Maximum delay response	1 ms	
Diameter	12 mm	
Length	1169 mm	

Environment

Product certifications	CE[RETURN]cCSAus[RETURN]UKCA
Ambient air temperature for operation	-1055 °C
Ambient air temperature for storage	-2070 °C
IP degree of protection	IP50 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.0 cm
Package 1 Width	9.0 cm
Package 1 Length	120.0 cm
Package 1 Weight	0.8 kg

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

