

XUY245CB2D2

Photoelectric sensors XU, Roller Sensor 245 mm N2, P93.1 IP65 Diam 8 Cable 2 m,Wires



Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	Application
Electronic sensor type	Photo-electric sensor
Sensor name	XUY
Sensor design	Roller sensor
Detection system	Diffuse
Type of output signal	Discrete
Discrete output type	PNP
Product specific application	Conveyor system

Complementary

Maximum voltage drop	<2 V at 100 mA (closed state)
Length	245 mm

Environment

Product certifications	CE[RETURN]cULus
Ambient air temperature for operation	0...50 °C
Ambient air temperature for storage	-20...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	6.0 cm
Package 1 Length	40.0 cm
Package 1 Weight	100.0 g

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com