XZCRV2609V3L15

Jumper cable PVC 4 W m8 f straight m8 m straight



Main

Accessory / separate part categor	Cabling accessory	
Accessory / separate part type	Jumper cable	

Complementary

- Completification y		
Jumper cable end 1	M8 male 4 pins straight connector with screw-on	
Jumper cable end 2	M8 female 3 pins straight connector with screw-on	
Collar material	Metal	
Cable composition	3 x 0.25 mm ²	
Cable length	15 m	
Wire insulation material	PVC	
Cable outer diameter	4.6 mm	
[Ue] rated operational voltage	250 V AC 300 V DC	
[In] rated current	3 A	
Insulation resistance	>= 1000 MOhm	
Maximum resistance across terminals	5000 mOhm	
Net weight	0.09 kg	

Environment

IP degree of protection	IP65 IP67
Product certifications	cULus
Ambient air temperature for operation	-2580 °C static
Ambient air temperature for storage	-2580 °C

Packing Units

3 - 3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.000 cm	
Package 1 Width	16.500 cm	
Package 1 Length	20.000 cm	
Package 1 Weight	476.000 g	

Offer Sustainability

•	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Robs enquiries contact us at	sustainability@tesensors.com