## XZCRV2705037L10

# Jumper cable PVC 3 W m8 f straight m8 m straight



#### Main

Accessory / separate part categor	Cabling accessory	
Accessory / separate part type	Jumper cable	

#### Complementary

Jumper cable end 1	M8 male 3 pins straight connector with screw-on
Jumper cable end 2	M8 female 3 pins straight connector with screw-on
Collar material	Metal
Cable composition	3 x 0.25 mm²
Cable length	10 m
Wire insulation material	PVC
Cable outer diameter	5.2 mm
[Ue] rated operational voltage	250 V AC 300 V DC
[In] rated current	3 A
Insulation resistance	>= 1000 MOhm
Maximum resistance across terminals	5000 mOhm
Net weight	0.1 kg

#### **Environment**

IP degree of protection	IP65 IP67
Product certifications	cULus
Ambient air temperature for operation	-2580 °C static
Ambient air temperature for storage	-2580 °C

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.0 cm	
Package 1 Width	16.5 cm	
Package 1 Length	20.0 cm	
Package 1 Weight	152.0 g	
Unit Type of Package 2	S02	
Number of Units in Package 2	10	
Package 2 Height	15.0 cm	
Package 2 Width	30.0 cm	
Package 2 Length	40.0 cm	
Package 2 Weight	1.975 kg	

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

