



Main

Range of product	Acti 9
Product name	Acti 9 iSO
Product or component type	Bell
Device short name	ISO

Complementary

[Us] rated supply voltage	230 V AC at 50/60 Hz
Power consumption in VA	5 VA
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	72 mm
Product weight	77 g
Auxiliary connection terminal	Tunnel type terminalsrigid 4 mm ² Tunnel type terminalsflexible 4 mm ² Tunnel type terminalsflexible with ferrule 4 mm ²
Wire stripping length	12 mm for bottom connection
Tightening torque	1.3 N.m bottom

Environment

Noise level	80 dB
Type of sound	Bell
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Ambient air temperature for operation	-10...40 °C
Ambient air temperature for storage	-25...60 °C

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant

EU RoHS Declaration

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------