



Main

Range	Acti 9
Product or component type	Shunt trip release with OC contact
Device short name	IMX+OF
Signal contacts composition	1 C/O
[Ie] rated operational current	DC-12 : 6 A at 24 V DC DC-12 : 6 A at 12 V DC AC-12 : 6 A at 24 V AC - 50 Hz AC-12 : 6 A at 12 V AC - 50 Hz
Control circuit voltage	24 V DC 12 V DC 24 V AC 50/60 Hz 12 V AC 50/60 Hz
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigì ARA RCA

Complementary

Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 1 cable(s) 4 mm² flexible Clamp terminal 2 cable(s) 2.5 mm² rigid Clamp terminal 1 cable(s) 6 mm² rigid Clamp terminal 2 cable(s) 2.5 mm² flexible with cable end
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------