



### Main

|                            |                                                                                        |
|----------------------------|----------------------------------------------------------------------------------------|
| Range                      | Acti 9                                                                                 |
| Product or component type  | Overvoltage release                                                                    |
| Device short name          | IMSU                                                                                   |
| Control circuit voltage    | 230 V AC 50/60 Hz                                                                      |
| Threshold tripping voltage | 275 V                                                                                  |
| 9 mm pitches               | 2                                                                                      |
| Product compatibility      | IC60<br>IID<br>Single terminal<br>Double terminal<br>ISW-NA<br>IDPN Vigi<br>ARA<br>RCA |

### Complementary

|                         |                                                                                                                                                                                                                                               |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local signalling        | Action indicator                                                                                                                                                                                                                              |
| Mounting mode           | Clip-on                                                                                                                                                                                                                                       |
| Mounting support        | DIN rail                                                                                                                                                                                                                                      |
| Width                   | 18 mm                                                                                                                                                                                                                                         |
| Colour                  | White                                                                                                                                                                                                                                         |
| Connections - terminals | Clamp terminal 2 cable(s) 2.12 mm <sup>2</sup> flexible with cable end<br>Clamp terminal 1 cable(s) 11 mm <sup>2</sup> flexible<br>Clamp terminal 2 cable(s) 2.12 mm <sup>2</sup> rigid<br>Clamp terminal 1 cable(s) 13 mm <sup>2</sup> rigid |
| Tightening torque       | 1 N.m                                                                                                                                                                                                                                         |

### Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Standards                             | EN/IEC 60947-5-1                 |
| Tropicalisation                       | 2 conforming to EN/IEC 60947-5-1 |
| Relative humidity                     | 95 % at 55 °C                    |
| Ambient air temperature for operation | -25...50 °C                      |
| Ambient air temperature for storage   | -40...85 °C                      |

### Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS (date code: YYWW)           | Compliant - since 1216 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available                                                                             |
| Product end of life instructions | Available <a href="#">Download End Of Life Manual</a>                                 |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|