

Main

Range	Acti 9
Product or component type	Voltage release
Device short name	IMNV

Complementary

Control circuit voltage	230 V AC 50 Hz
Threshold tripping voltage	280 V +/- 5 % AC
Control threshold undervoltage	50...160 V
Control type	Toggle
Mounting location	Left side of circuit-breaker
9 mm pitches	2
Height	86.18 mm
Width	18 mm
Depth	74.5 mm
Product weight	75 g
Connections - terminals	Tunnel type terminals, bottom. flexible(with cable end): 2 x 1.5 mm ² Tunnel type terminals, bottom. rigid(without cable end): 2 x 2.5 mm ² Tunnel type terminals, bottom. flexible(without cable end): 1 x 0.5...4 mm ² Tunnel type terminals, bottom. rigid(without cable end): 1 x 1...6 mm ²
Wire stripping length	10 mm(bottom)
Tightening torque	1 N.m(bottom)
Product compatibility	IDPN IID ARA RCA iC65

Environment

Standards	IEC 60947-1
Quality labels	CE
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1219 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available