



Main

Range of product	Acti 9
Device short name	iATLz
Product or component type	Impedance adaptation auxiliary
[Uc] control circuit voltage	130...240 V AC 50/60 Hz

Complementary

Remote control type	Illuminated push-button 3 mA
Mounting mode	Fixed, on left side of TL
Mounting support	DIN rail
9 mm pitches	2
Height	86 mm
Width	18 mm
Depth	71 mm
Colour	White
Connections - terminals	Tunnel type terminals0.5...4 mm ² - rigid Tunnel type terminals0.5...4 mm ² - rigid - with cable end Tunnel type terminals1...4 mm ² - flexible Tunnel type terminals1...4 mm ² - flexible - with cable end
Wire stripping length	11 mm
Tightening torque	1 N.m
Range compatibility	Acti 9 iTL iTL Acti 9 iTL iTLi Acti 9 iTL iTLs Acti 9 iTL iTLc
Product compatibility	ITL (32 A) ITL (16 A)

Environment

Overvoltage category	III
Tropicalisation	2

Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...70 °C
Standards	EN/IEC 60669-2-2

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------