



Main

Range	Acti 9
Product or component type	Time delay auxiliary
Device short name	iATEt
[Uc] control circuit voltage	24...110 V DC impulse 24...240 V AC 50/60 Hz maintained

Complementary

Type of setting	Time delay configuration
Time delay range	2 s...10 min 2 s...10 h 6...60 s 1...10 s 6 s...1 h
Maximum output current	0.2 A holding 3 A inrush
Hold-in power consumption in VA	5 VA
Mounting mode	Fixed, on the left of TL or CT
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	White
Overvoltage category	III
[Uimp] rated impulse withstand voltage	4 kV
[Ui] rated insulation voltage	440 V
Standards	EN/IEC 60669-2-2
Connections - terminals	Output connection: yellow clips Input connection: tunnel type terminals 2 cable(s) 2.5 mm² flexible Input connection: tunnel type terminals 2 cable(s) 1.5 mm² rigid
Wire stripping length	9 mm

Tightening torque	0.8 N.m
Range compatibility	Acti9 iCT Acti9 iTL
Market segment	Small commercial Residential
Compatibility code	IATet

Environment

IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	40...80 °C

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------