



Main

Range of product	ICT
Range	Acti 9
Device short name	iACTs
Product or component type	Remote indication auxiliary
Signal contacts composition	2 NO

Complementary

Signalling circuit voltage	24 V AC/DC: 10 mA 230 V AC: 50/60 Hz 5 A 230 V AC: 50/60 Hz 2 A 130 V DC: 1 A
[Uc] control circuit voltage	24...240 V AC 50/60 Hz 24...130 V DC
Range compatibility	Acti 9 iCT
[Ui] rated insulation voltage	440 V
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Fixed, on the right of CT
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	1
Height	81 mm
Width	9 mm
Depth	68 mm
Colour	White
Auxiliary connection terminal	Tunnel type terminals2 cable(s) flexible 2.5 mm ² Tunnel type terminals2 cable(s) rigid 1.5 mm ² Tunnel type terminals1 cable(s) rigid 1.5...2.5 mm ² Tunnel type terminals1 cable(s) flexible 1.5...2.5 mm ²
Wire stripping length	9 mm
Tightening torque	0.8 N.m
Product compatibility	ICT
Market segment	Residential

	Small commercial
Compatibility code	IACTs

Environment

Standards	EN 60947-5
IP degree of protection	IP20 IP20 conforming to IEC 60529
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...70 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------