Product datasheet Characteristics

A9C15918

Acti 9 overvoltage protection auxiliary iACTp 48...127 V AC



man	
Range	Acti 9
Product or component type	Overvoltage protection auxiliary (2 circuits)
Device short name	IACTp
[Uc] control circuit voltage	48127 V AC 50/60 Hz

Complementary

Range	Acti 9	
Product or component type	Overvoltage protection auxiliary (2 circuits)	
Device short name	IACTp	
[Uc] control circuit voltage	48127 V AC 50/60 Hz	
Complementary		
Hold-in power consumption in VA	3 VA	
Mounting mode	Fixed, on the left of CT	
Mounting support	DIN rail	
9 mm pitches	2	
Height	81 mm	
Width	18 mm	
Depth	60 mm	
Colour	White	
Overvoltage category	III	
[Uimp] rated impulse withstand voltage	4 kV	
[Ui] rated insulation voltage	440 V	
Standards	IEC/EN 61095	
Connections - terminals	Control circuit: tunnel type terminals 2 cable(s) 2.5 mm² flexible Control circuit: tunnel type terminals 2 cable(s) 1.5 mm² rigid Control circuit: yellow clips	
Market segment	Small commercial Residential	
Compatibility code	IACTp	
Environment		
IP degree of protection	IP20 conforming to IEC 60529	
	-550 °C	
Ambient air temperature for operation	-550 C	

Environment

IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-550 °C
Ambient air temperature for storage	4070 °C

Offer Sustainability

REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months