# Product datasheet Characteristics

### A9C64440

## Reflex iC60H Ti24 40 A 4P curve B integrated control MCB



Price\*: 398.06 GBP



#### Main

IVIAIII		ţ.
Device application	Distribution Control	9
Range	Acti 9	
Product name	Reflex iC60	***************************************
Device short name	Reflex iC60H	± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ±
Product or component type	Integrated control circuit breaker	
Poles description	4P	,
Number of protected poles	4	
Network type	AC	
Trip unit technology	Thermal-magnetic	
Curve code	В	

### Complementary

[In] rated current	40 A	
Network frequency	50/60 Hz	
Breaking capacity code	Н	<u>۔</u> 2
Breaking capacity	30 kA Icu at 220240 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 kA Icu at 380415 V AC 50/60 Hz conforming to EN/IEC 60947-2	;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;
[Ui] rated insulation voltage	500 V AC	
Contact position indicator	Yes	
Control type	Remote control by pulse ON/OFF button Remote control by continuous command Toggle	
Control signal type	Maintained very low voltage Maintained Impulse	i.e.
Local signalling	Red LED: fault Flashing LED: device ready	; ; ;

	Flashing LED: device tripped Flashing LED: device overheat Green LED: device ON
[Uc] control circuit voltage	230 V AC 50/60 Hz 24 V AC 50/60 Hz 48 V AC 50/60 Hz 24 V DC 48 V DC
[Us] rated supply voltage	230 V AC at 50/60 Hz
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	13
Height	84 mm
Width	117 mm
Depth	77 mm
Colour	White
Mechanical durability	50000 cycles
Electrical durability	AC-1: 50000 cycles AC 50 Hz
Provision for padlocking	Padlockable
Locking options description	Padlock in OFF position
Earth-leakage protection	Separate block
Product compatibility	With PLC
Environment	
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	3
Tropicalisation	2
Relative humidity	93 % at 40 °C

Offer	Sus	taina	hili	tv
Onci	Ous	tania		L y

Green Premium product	
REACh Declaration	
Compliant EU RoHS Declaration	
Yes	
Yes	
China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Product Environmental Profile	
End of Life Information	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

#### Contractual warranty

	•	
Warranty		18 months