



### Main

|                           |                                                                                                                                                                                                                                                                                                                                                                                     |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device application        | Motor                                                                                                                                                                                                                                                                                                                                                                               |
| Range                     | Acti 9                                                                                                                                                                                                                                                                                                                                                                              |
| Product or component type | Miniature circuit-breaker                                                                                                                                                                                                                                                                                                                                                           |
| Product name              | IC60                                                                                                                                                                                                                                                                                                                                                                                |
| Device short name         | IC60L                                                                                                                                                                                                                                                                                                                                                                               |
| Poles description         | 2P                                                                                                                                                                                                                                                                                                                                                                                  |
| Number of protected poles | 2                                                                                                                                                                                                                                                                                                                                                                                   |
| [In] rated current        | 16 A                                                                                                                                                                                                                                                                                                                                                                                |
| Network type              | AC                                                                                                                                                                                                                                                                                                                                                                                  |
| Trip unit technology      | Magnetic                                                                                                                                                                                                                                                                                                                                                                            |
| Curve code                | MA                                                                                                                                                                                                                                                                                                                                                                                  |
| Breaking capacity         | 40 kA Icu conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz<br>40 kA Icu conforming to EN 60947-2 - 220...240 V AC 50/60 Hz<br>20 kA Icu conforming to IEC 60947-2 - 380...415 V AC 50/60 Hz<br>20 kA Icu conforming to EN 60947-2 - 380...415 V AC 50/60 Hz<br>15 kA Icu conforming to IEC 60947-2 - 440 V AC 50/60 Hz<br>15 kA Icu conforming to EN 60947-2 - 440 V AC 50/60 Hz |
| Utilisation category      | Category A conforming to IEC 60947-2<br>Category A conforming to EN 60947-2                                                                                                                                                                                                                                                                                                         |
| Suitability for isolation | Yes conforming to IEC 60947-2<br>Yes conforming to EN 60947-2                                                                                                                                                                                                                                                                                                                       |
| Standards                 | EN 60947-2<br>IEC 60947-2                                                                                                                                                                                                                                                                                                                                                           |

### Complementary

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network frequency                      | 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Magnetic tripping limit                | 12 x In +/- 20 %                                                                                                                                                                                                                                                                                                                                                                                                                |
| [Ics] rated service breaking capacity  | 20 kA 50 % x Icu conforming to IEC 60947-2 - 220...240 V AC 50/60 Hz<br>20 kA 50 % x Icu conforming to EN 60947-2 - 220...240 V AC 50/60 Hz<br>7.5 kA 50 % x Icu conforming to IEC 60947-2 - 440 V AC 50/60 Hz<br>10 kA 50 % x Icu conforming to IEC 60947-2 - 380...415 V AC 50/60 Hz<br>7.5 kA 50 % x Icu conforming to EN 60947-2 - 440 V AC 50/60 Hz<br>10 kA 50 % x Icu conforming to EN 60947-2 - 380...415 V AC 50/60 Hz |
| Limitation class                       | 3 conforming to IEC 60898-1<br>3 conforming to EN 60898-1                                                                                                                                                                                                                                                                                                                                                                       |
| [Ui] rated insulation voltage          | 500 V AC 50/60 Hz conforming to IEC 60947-2<br>500 V AC 50/60 Hz conforming to EN 60947-2                                                                                                                                                                                                                                                                                                                                       |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-2<br>6 kV conforming to EN 60947-2                                                                                                                                                                                                                                                                                                                                                                 |
| Contact position indicator             | Yes                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Control type                           | Toggle                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Local signalling                       | Trip indicator                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Mounting mode                          | Fixed                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Mounting support                       | DIN rail                                                                                                                                                                                                                                                                                                                                                                                                                        |

|                                              |                                                                                                                                                       |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Comb busbar distribution block compatibility | YES top or bottom                                                                                                                                     |
| 9 mm pitches                                 | 4                                                                                                                                                     |
| Height                                       | 85 mm                                                                                                                                                 |
| Width                                        | 36 mm                                                                                                                                                 |
| Depth                                        | 78.5 mm                                                                                                                                               |
| Product weight                               | 0.25 kg                                                                                                                                               |
| Colour                                       | White                                                                                                                                                 |
| Mechanical durability                        | 20000 cycles                                                                                                                                          |
| Electrical durability                        | 10000 cycles                                                                                                                                          |
| Connections - terminals                      | Single terminal, top or bottom flexible wire(s) 1...16 mm <sup>2</sup> max<br>Single terminal, top or bottom rigid wire(s) 1...25 mm <sup>2</sup> max |
| Wire stripping length                        | 14 mm top or bottom                                                                                                                                   |
| Tightening torque                            | 2 N.m top or bottom                                                                                                                                   |
| Earth-leakage protection                     | Separate block                                                                                                                                        |

## Environment

|                                       |                                                             |
|---------------------------------------|-------------------------------------------------------------|
| IP degree of protection               | IP20 conforming to EN 60529<br>IP20 conforming to IEC 60529 |
| Pollution degree                      | 3 conforming to IEC 60947-2<br>3 conforming to EN 60947-2   |
| Overvoltage category                  | IV                                                          |
| Tropicalisation                       | 2 conforming to IEC 60068-1                                 |
| Relative humidity                     | 95 % ( 55 °C )                                              |
| Operating altitude                    | 0...2000 m                                                  |
| Ambient air temperature for operation | -35...70 °C                                                 |
| Ambient air temperature for storage   | -40...85 °C                                                 |

## Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS (date code: YYWW)           | Compliant - since 1001 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available                                                                             |
| Product end of life instructions | Need no specific recycling operations                                                 |