



### Main

|                           |                                                                                  |
|---------------------------|----------------------------------------------------------------------------------|
| Range                     | Acti 9<br>Clario<br>Librio<br>Prodis                                             |
| Product or component type | Undervoltage release                                                             |
| Device short name         | MN                                                                               |
| Control circuit voltage   | 115 V AC 400 Hz                                                                  |
| Control type              | Standard                                                                         |
| 9 mm pitches              | 2                                                                                |
| Product compatibility     | C40<br>C60<br>DT40<br>IDPN<br>DT60<br>C120<br>DPN Vigi<br>ITG40<br>IDc<br>ID C40 |

### Complementary

|                         |                                                                                                                                                                                                                                |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local signalling        | Action indicator                                                                                                                                                                                                               |
| Mounting mode           | Fixed                                                                                                                                                                                                                          |
| Mounting support        | 35 mm symmetrical DIN rail                                                                                                                                                                                                     |
| Height                  | 82.5 mm                                                                                                                                                                                                                        |
| Width                   | 18 mm                                                                                                                                                                                                                          |
| Depth                   | 68 mm                                                                                                                                                                                                                          |
| Colour                  | White                                                                                                                                                                                                                          |
| Connections - terminals | Clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> rigid<br>Clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> flexible<br>Clamp terminal 1 cable(s) 2.5 mm <sup>2</sup> rigid<br>Clamp terminal 1 cable(s) 2.5 mm <sup>2</sup> flexible |
| Wire stripping length   | 9 mm                                                                                                                                                                                                                           |
| Tightening torque       | 1 N.m                                                                                                                                                                                                                          |

### Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Standards                             | EN/IEC 60947-5-1                 |
| Product certifications                | ASEFA<br>ASTA<br>KEMA<br>LCIE    |
| Tropicalisation                       | 2 conforming to EN/IEC 60947-5-1 |
| Relative humidity                     | 95 % at 55 °C                    |
| Ambient air temperature for operation | -25...50 °C                      |
| Ambient air temperature for storage   | -40...85 °C                      |

### Offer Sustainability

|                          |                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status | Not Green Premium product                                                             |
| RoHS                     | Compliant - since 1216 - <a href="#">Schneider Electric declaration of conformity</a> |