



Main

Range	Acti 9 Clario Librio Prodis
Product or component type	Undervoltage release
Device short name	MNs
Control circuit voltage	220...240 V AC 50/60 Hz
Control type	Delayed
9 mm pitches	2
Product compatibility	C40 C60 DT40 IDPN DT60 C120 DPN Vigi ITG40 IDc ID C40

Complementary

Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Colour	White
Connections - terminals	Clamp terminal 2 cable(s) 1.5 mm ² rigid Clamp terminal 2 cable(s) 1.5 mm ² flexible Clamp terminal 1 cable(s) 2.5 mm ² rigid Clamp terminal 1 cable(s) 2.5 mm ² flexible
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1216 - Schneider Electric declaration of conformity