



Main

Device application	Distribution
Range of product	Acti 9
Range	Acti 9
Product name	IDPN
Product or component type	Miniature circuit-breaker
Device short name	IDPNN
Poles description	1P + N
Number of protected poles	1
Neutral position	Left
[In] rated current	32 A (Tref=30 °C)
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	Icn=6 kA (230 V AC, 50/60 Hz, conforming to IEC 60898-1)
Utilisation category	Category A (conforming to IEC 60947-2)
Suitability for isolation	Yes (conforming to IEC 60947-2)

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V, AC 50/60 Hz
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	Ics=6 kA, (Ics=100 %Icn/Icu, conforming to IEC 60898-1), 230 V AC, 50/60 Hz
Limitation class	3 conforming to IEC 60898-1
[Ui] rated insulation voltage	400 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	4 kV (conforming to IEC 60947-2)
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	2
Height	94 mm
Width	18 mm
Depth	74 mm
Product weight	122 g
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Connections - terminals	Rigid, without cable end: 1...16 mm². (tunnel type terminals, top or bottom) Flexible, with or without cable end: 1...16 mm². (tunnel type terminals, top or bottom)
Wire stripping length	14 mm power circuit
Tightening torque	2 N.m power circuit
Earth-leakage protection	Separate block

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company Schneider Electric. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	IEC 60898-1 GB 10963.1
Product certifications	CCC CE
IP degree of protection	IP20 (conforming to IEC 60529)
Pollution degree	2 (conforming to IEC 60947-2)
Tropicalisation	2 (conforming to IEC 60068-1)
Relative humidity	95 % 55 °C
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...80 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1111 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations