



## Main

|                                    |                                     |
|------------------------------------|-------------------------------------|
| Range                              | Linergy                             |
| Product name                       | FH                                  |
| Product or component type          | Comb busbar                         |
| Accessory / separate part category | Connection accessory                |
| Poles description                  | 2P                                  |
| Number of ways                     | 6 ways, type : 2 L with 18 mm pitch |
| Distance between way               | 36 mm                               |
| Poles distribution                 | N L                                 |
| Connector type                     | Tooth                               |
| Length in 18 mm modules            | 12                                  |

## Complementary

|                                |                                                                   |
|--------------------------------|-------------------------------------------------------------------|
| Device presentation            | Cuttable                                                          |
| [In] rated current             | 100 A ( 40 °C )                                                   |
| [Ue] rated operational voltage | 415 V AC                                                          |
| [Ui] rated insulation voltage  | 500 V AC conforming to IEC 61439-2                                |
| Mounting mode                  | Horizontal                                                        |
| 9 mm pitches                   | 24                                                                |
| Width                          | 220 mm                                                            |
| Colour                         | Anthracite grey ( RAL 7016 )                                      |
| Range compatibility            | Acti 9                                                            |
| Product compatibility          | IC60<br>IID<br>ISW-NA<br>IK60<br>IID K<br>ISW switch disconnecter |

## Environment

|                 |                                             |
|-----------------|---------------------------------------------|
| Standards       | IEC 60947-7-1<br>IEC 61439-2                |
| Fire resistance | 960 °C ( 30 s ) conforming to IEC 60695-2-1 |

## Offer Sustainability

|                          |                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status | Not Green Premium product                                                             |
| RoHS (date code: YYWW)   | Compliant - since 1336 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                    | Reference not containing SVHC above the threshold                                     |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|