



### Main

|                                     |                                             |
|-------------------------------------|---------------------------------------------|
| Range                               | Acti 9                                      |
| Product or component type           | Earth leakage add-on block                  |
| Device short name                   | Vigi iPN                                    |
| Poles description                   | 1P + N                                      |
| Neutral position                    | Left                                        |
| [In] rated current                  | 40 A                                        |
| Earth-leakage sensitivity           | 10 mA                                       |
| Earth-leakage protection time delay | Instantaneous                               |
| Earth leakage protection type       | Class A                                     |
| Network type                        | AC                                          |
| Network frequency                   | 50/60 Hz                                    |
| [Ue] rated operational voltage      | 230 V AC 50/60 Hz conforming to GB 16917.22 |
| Standards                           | GB 16917.22                                 |
| 9 mm pitches                        | 2                                           |

### Complementary

|                                      |                               |
|--------------------------------------|-------------------------------|
| Device location in system            | Outgoer                       |
| Overvoltage protection               | Without                       |
| Residual current tripping technology | Voltage dependent             |
| Local signalling                     | Trip indicator                |
| Mounting mode                        | Clip-on                       |
| Mounting support                     | DIN rail                      |
| Electrical connection to mcb         | By screws                     |
| Width                                | 36 mm                         |
| Colour                               | White                         |
| Connections - terminals              | Tunnel type terminal downside |

### Environment

|                         |      |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

### Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS (date code: YYWW)           | Compliant - since 1111 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available                                                                             |
| Product end of life instructions | Available                                                                             |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|