

ABE9C1241L05

IP67 passive splitter box - cable 5 m - with 4 channels M12 connector - Led



Main


Range of product	Advantys ABE9
Product or component type	IP67 passive splitter box
Number of channels	4
Electrical connection	4 female connectors M12 5 pins 1 pre-wired cable connector 5 m
Status LED	2 LEDs green power ON 1 LED per channel yellow channel status

Complementary


Number of ways	8 ways
[Ue] rated operational voltage	24 V DC
Current per channel	≤ 4 A
Insulation group	Category 3 VDE 0110
Operating position	Any position
Fixing mode	M4 screw fixing
Contact resistance	5000 µOhm
Current of common	12 A 0.75 mm ² 16 A 1 mm ²
Separation of commons	Without or with
Product weight	0.68 kg

Environment

IP degree of protection	IP67 IEC 529
Product certifications	CULus
Ambient air temperature for operation	-20...80 °C
Ambient air temperature for storage	-40...85 °C
Vibration resistance	0.2 gn 57...150 Hz IEC 68-2-6, FC tests
Shock resistance	30 gn 11 ms IEC 68-2-2 30 gn 11 ms EN 68-2-2

$$\frac{\text{mm}}{\text{in.}}$$


Wiring Diagram



(1) BR1 and BR2: removable link

Item	Terminal	Wire
1/4	1	White
1/2	9	Grey/pink
2/4	2	Green
2/2	10	Red/blue
3/4	3	Yellow
3/2	11	White/green
4/4	4	Grey
4/2	12	Brown/green
1 and 3/1	+1	Brown 1
2 and 4/1	+2	Brown 2
1 and 3/3	-1	Blue 1
2 and 4/3	-2	Blue 2
1...4/5	PE	Green/yellow

Connection Terminals

