


AS-Interface ClassicLine module with quick mounting technology

ClassicLine 4DI-Y AUX 4DO-Y


Application

Application	only for operation with AS-i masters with the profile M4
-------------	--

Electrical data

Operating voltage	[V]	26.5...31.6 DC; ("supply class 2" to cULus)
Max. current consumption from AS-i	[mA]	30
Max. current load total	[A]	3
Integrated watchdog		yes

Inputs

Number of digital inputs		4
Input circuit of digital inputs		PNP
voltage supply	[V]	20...30; (via flat cable)
Max. total current rating of inputs	[mA]	1000
Input current High	[mA]	6...10
Input current Low	[mA]	0...2
Min. switching level high signal	[V]	11
Electrically separated		yes
Digital inputs protected against short circuits		yes
Sensor supply of the inputs		to PELV



AS-Interface ClassicLine module with quick mounting technology

ClassicLine 4DI-Y AUX 4DO-Y

Outputs					
Number of digital outputs	4				
Beschaltung	PNP				
Voltage range DC	20...30; (to PELV; via flat cable)				
Max. current load per output [mA]	1000; (utilisation category DC-13 (control of electromagnets): 20 W (IEC 60947-5-1))				
Short-circuit proof	yes				
Electrically separated	yes				
Operating conditions					
Ambient temperature [°C]	-25...70				
Protection	IP 67				
Tests / approvals					
EMC	EN 50295				
	IEC 61000-6-2				
AS-i classification					
AS-i version	3.0				
AS-i addressing	addressing socket				
Extended addressing mode possible	yes				
AS-i profile	S-7.A.7				
AS-i I/O configuration [hex]	7				
AS-i ID code [hex]	A.7				
AS-i certificate pending	yes				
Assignment of the data bits	data bit	D0	D1	D2	D3
	input	1	2	3	4
	socket	I-1/2	I-1/2 I-2	I-3/4	I-3/4 I-4
	pin	4	2 4	4	2 4
	Output	1	2	3	4
	socket	O-1/2	O-1/2 O2	O-3/4	O-3/4 O-4
	pin	4	2 4	4	2 4
Mechanical data					
Weight [g]	287.4				
Type of mounting	AS-i flat cables directly connectable				
Materials	PA; piercing contacts: CuSn6 nickel-plated and tin-plated;				
Displays / operating elements					
Display	operation		LED, green Voltage AUX > 7 V		
	errors		LED, red AUX 15 V ± 2 V		
	function		LED, yellow		
Accessories					
Accessories (supplied)	lower part				
Accessories (optional)	Protective cap: M12, E73004				
Remarks					
Pack quantity	1 pcs.				



AS-Interface ClassicLine module with quick mounting technology


ClassicLine 4DI-Y AUX 4DO-Y

Electrical connection

quick mounting technology for AS-i flat cable: ; three orientations possible

Electrical connection - Outputs

Connection






AS-Interface ClassicLine module with quick mounting technology

ClassicLine 4DI-Y AUX 4DO-Y

Outputs	
socket O-1/2	
1	not used
2	switching output 2
3	external voltage AUX -
4	switching output 1
5	not used
socket O-2	
1	not used
2	not used
3	external voltage AUX -
4	switching output 2
5	not used
socket O-3/4	
1	not used
2	switching output 4
3	external voltage AUX -
4	switching output 3
5	not used
socket O-4	
1	not used
2	not used
3	external voltage AUX -
4	switching output 4
5	not used

Connector: M12





AS-Interface ClassicLine module with quick mounting technology

ClassicLine 4DI-Y AUX 4DO-Y

Inputs	
socket I-1/2	
1	Sensor supply L+
2	data input 2
3	Sensor supply L-
4	data input 1
5	not used
socket I-2	
1	Sensor supply L+
2	not used
3	Sensor supply L-
4	data input 2
5	not used
socket I-3/4	
1	voltage supply L+
2	data input 4
3	Sensor supply L-
4	data input 3
5	not used
socket I-4	
1	Sensor supply L+
2	not used
3	Sensor supply L-
4	data input 4
5	not used

Connector: M12