



Main

Range of product	Advantys
Product or component type	Direct connection interface
Range compatibility	AS-Interface cabling system
AS-i version	V2.1
Addressing	Standard
Enclosure type	Compact
Width	45 mm
Number of addresses	<= 31
Number of inputs	2
Number of outputs	2

Complementary

Height	116.5 mm for connection base ASI67FFB02 80 mm for connection base ASI67FFB01
Depth	37.5 mm for connection base ASI67FFB02 42 mm for connection base ASI67FFB01
[Us] rated supply voltage	26.5...31.6 V for AS-Interface line
Reverse polarity protection	Integrated
Current consumption	<= 32 mA AS-Interface line without sensor supply
AS-i profile	30FE
Output fallback position	OFF in the absence of communication
Parameter bits	Not used
Electrical connection	2 female connectors M12 standard for sensor 2 female connectors M12 standard for actuator 1 jack connector 1 IDC for auxiliary supply 1 IDC for AS-Interface line
Supply	Via AS-Interface line for sensor side By external supply for actuator side
Input compatibility	2 or 3-wire PNP conforming to EN/IEC 61131-2 type 2
Sensor power supply	18...30 V conforming to EN/IEC 60947-5-1
Supply current for sensors	<= 100 mA
Voltage state 1 guaranteed	> 11 V (sensor side)
Current state 1 guaranteed	> 6 mA (sensor side)
Voltage state 0 guaranteed	< 5 V (sensor side)
Current state 0 guaranteed	< 2 mA (sensor side)
Input current	8 mA
Output type	Solid state (PNP transistor)
Output voltage	21.6...27.2 V
Drop-out voltage	<= 1 V at I _n
Thermal current per channel	4 A at < 40 °C (actuator side) 2 A at 40...70 °C (actuator side)
Thermal current per common	2 A (actuator side)
Leakage current	<= 0.012 mA
Output overload protection	Thermal integrated
Output short-circuit protection	Thermal integrated
Nominal output current	2 A DC-13 2 A DC-12

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Switching time	< 20 ms for ON to OFF (actuator side) < 20 ms for OFF to ON (actuator side)
Installation category	II conforming to IEC 60664
Surge withstand	2 kV at 12 Ohm (common mode) conforming to EN/IEC 61000-4-5 1 kV at 2 Ohm (differential mode) conforming to EN/IEC 61000-4-5
Fixing mode	Clip-on, mounting on 35 mm symmetrical rail conforming to EN/IEC 60715 By 2 or 3 screws M4
Tightening torque	0.6 N.m
Material	Stainless steel
Housing material	PBT 30 % GF Valox 553
Local signalling	4 LEDs yellow, function: input/output status 1 LED red, function: fault 1 LED green, function: auxiliary supply ON (AUX PWR) 1 LED green, function: AS-Interface power ON (ASI PWR)
Product weight	0.09 kg

Environment

Product certifications	AS-Interface No 55101 CSA UL
Ambient air temperature for operation	-25...70 °C conforming to EN/IEC 60529
Ambient air temperature for storage	-40...85 °C
IP degree of protection	IP67 conforming to IEC 60529 IP54 for use as tap-off or at line end conforming to IEC 60529
Shock resistance	30 gn for 11 ms conforming to IEC 60068-2-27
Vibration resistance	5 gn (f = 36...150 Hz) conforming to EN/IEC 60068-2-6 0.7 gn (f = 13.2...100 Hz) conforming to GL +/-1 mm (f = 2...36 Hz) conforming to EN/IEC 60068-2-6 +/-1 mm (f = 2...13.2 Hz) conforming to GL
Dielectric test voltage	0.5 kV between inputs and outputs for 1 minute conforming to EN/IEC 60664-1 0.5 kV between inputs and auxiliary supply for 1 minute conforming to EN/IEC 60664-1 0.5 kV between auxiliary supply and AS-Interface line for 1 minute conforming to EN/IEC 60664-1 2 kV between outputs and AS-Interface line for 1 minute conforming to EN/IEC 60664-1
Resistance to electrostatic discharge	8 kV conforming to EN/IEC 61000-4-2 level 3
Resistance to radiated fields	10 V/m conforming to EN/IEC 61000-4-3 level 3
Resistance to conducted disturbances, induced by radio frequency fields	3 V conforming to EN/IEC 61000-4-6
Resistance to fast transients	2 kV conforming to EN/IEC 60100-4-4 level 3
Pollution degree	3 conforming to EN/IEC 60604-4-1
Fire resistance	At 750 °C, extinction time: < 30 s conforming to EN/IEC 60695-2-11