



Main

Product or component type	Interface for products with connector
Range compatibility	AS-Interface cabling system
Cable entry	2 entries, M12
Number of contacts	2
AS-Interface	0.B.F.F
Supply	Via AS-Interface

Complementary

Addressing	Using adjustment terminal
[Us] rated supply voltage	24 V DC (- 15...15 %)
Power consumption	1.2 W
Current consumption	45 mA AS-Interface line
Connections - terminals	1 connector M12 for AS-Interface line
Product weight	0.05 kg

Environment

Standards	EN 954-1 category 4 EN/IEC 60204-1 EN/IEC 60947-5-1 ISO 13849-1 category 4
Product certifications	CSA TÜV UL
IP degree of protection	IP67 conforming to IEC 60529
Ambient air temperature for operation	-10...55 °C
Ambient air temperature for storage	-25...85 °C
Shock resistance	10 gn
Vibration resistance	5 gn

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.