



Main

Range compatibility	Lexium 23 Plus
Product or component type	Servo motor
Device short name	BCH

Complementary

Maximum mechanical speed	5000 rpm
[Us] rated supply voltage	220 V
Network number of phases	Three phase
Continuous stall current	12.05 A
Continuous power	2 kW
Shaft end	Keyed
Second shaft	Without second shaft end
Shaft diameter	22 mm
Shaft length	37 mm
Key width	8 mm
Feedback type	20 bits incremental encoder
Holding brake	Without
Mounting support	Asian standard flange
Motor flange size	100 mm
Torque constant	0.53 N.m/A
Back emf constant	19.2 V/krpm at 20 °C
Rotor inertia	4.45 kg.cm ²
Stator resistance	0.26 Ohm at 20 °C
Stator inductance	3 mH at 20 °C
Stator electrical time constant	11.4 ms at 20 °C
Maximum radial force Fr	490 N
Maximum axial force Fa	98 N
Brake pull-in power	19.4 W
Type of cooling	Natural convection
Length	199 mm
Number of motor stacks	2

Centring collar diameter	95 mm
Centring collar depth	5 mm
Number of mounting holes	4
Mounting holes diameter	9 mm
Circle diameter of the mounting holes	115 mm
Distance shaft shoulder-flange	37 mm
Product weight	6.2 kg


Environment

IP degree of protection	IP65
Ambient air temperature for operation	0...40 °C

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions



(1) Shaft end, keyed slot (optional)
Dimensions in mm


c (without holding brake)	c (with holding brake)
199	226

Dimensions in in.

c (without holding brake)	c (with holding brake)
7.83	8.90

Torque/Speed Curves with 220 V Three Phase Supply Voltage

Servo Motor with LXM23•U20M3X Servo Drive



- M : Torque in Nm
- n : Speed in rpm
- 1 : Peak torque
- 2 : Continuous torque