



Main

Product or component type	Servo motor
Device short name	BMH
Maximum mechanical speed	4000 rpm
Continuous stall torque	37.4 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 37.4 N.m for LXM32.D72N4 at 24 A, 480 V, three phase 48 N.m for LXM32MD85N4 at 32 A, 400 V, three phase 48 N.m for LXM32MD85N4 at 32 A, 480 V, three phase 48 N.m for LXM32MC10N4 at 40 A, 400 V, three phase 48 N.m for LXM32MC10N4 at 40 A, 480 V, three phase
Peak stall torque	101 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 101 N.m for LXM32.D72N4 at 24 A, 480 V, three phase 115.5 N.m for LXM32MD85N4 at 32 A, 400 V, three phase 115.5 N.m for LXM32MD85N4 at 32 A, 480 V, three phase 130.7 N.m for LXM32MC10N4 at 40 A, 400 V, three phase 130.7 N.m for LXM32MC10N4 at 40 A, 480 V, three phase
Nominal output power	5900 W for LXM32.D72N4 at 24 A, 400 V, three phase 5900 W for LXM32.D72N4 at 24 A, 480 V, three phase 6070 W for LXM32MD85N4 at 32 A, 400 V, three phase 6070 W for LXM32MD85N4 at 32 A, 480 V, three phase 6070 W for LXM32MC10N4 at 40 A, 400 V, three phase 6070 W for LXM32MC10N4 at 40 A, 480 V, three phase
Nominal torque	22.3 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 22.3 N.m for LXM32.D72N4 at 24 A, 480 V, three phase 29 N.m for LXM32MD85N4 at 32 A, 400 V, three phase 29 N.m for LXM32MD85N4 at 32 A, 480 V, three phase 29 N.m for LXM32MC10N4 at 40 A, 400 V, three phase 29 N.m for LXM32MC10N4 at 40 A, 480 V, three phase
Nominal speed	2000 rpm for LXM32MC10N4 at 40 A, 400 V, three phase 2000 rpm for LXM32MC10N4 at 40 A, 480 V, three phase 2500 rpm for LXM32.D72N4 at 24 A, 400 V, three phase 2500 rpm for LXM32.D72N4 at 24 A, 480 V, three phase 2000 rpm for LXM32MD85N4 at 32 A, 400 V, three phase 2000 rpm for LXM32MD85N4 at 32 A, 480 V, three phase
Product compatibility	LXM32.D72N4 at 400...480 V three phase
Shaft end	Smooth shaft
IP degree of protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	131072 points/turn x 4096 turns
Holding brake	With

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting support	International standard flange
Electrical connection	Rotatable right-angled connectors

Complementary

Range compatibility	Lexion 32
[Us] rated supply voltage	480 V
Network number of phases	Three phase
Continuous stall current	30.8 A
Continuous power	6.1 W
Maximum current Irms	72 A for LXM32.D72N4
Maximum permanent current	114 A
Second shaft	Without second shaft end
Shaft diameter	38 mm
Shaft length	80 mm
Feedback type	Multiturn SinCos Hiperface
Holding torque	80 N.m holding brake
Motor flange size	190 mm
Number of motor stacks	2
Torque constant	1.56 N.m/A at 120 °C
Back emf constant	108.3 V/krpm at 120 °C
Number of motor poles	10
Rotor inertia	144.8 kg.cm²
Stator resistance	0.15 Ohm at 20 °C
Stator inductance	3.86 mH at 20 °C
Stator electrical time constant	25.7 ms at 20 °C
Maximum radial force Fr	4200 N at 1000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	40 W
Type of cooling	Natural convection
Length	310 mm
Centring collar diameter	180 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Product weight	32.5 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------