



Main

Range of product	Modicon M340 automation platform
Product or component type	Discrete output module
Product specific application	For severe environments
Electrical connection	20-way connector
Discrete output number	8 conforming to EN/IEC 61131-2
Discrete output type	Relay
Discrete output voltage	24...240 V 10...264 V AC 12...24 V 10...34 V DC

Complementary

[I _{th}] conventional free air thermal current	3 A
Insulation resistance	> 10 MOhm 500 V DC
Power dissipation in W	<= 2.7 W
Response time on output	<= 8 ms deactivation <= 10 ms activation
Typical current consumption	100 mA at 3.3 V DC
MTBF reliability	1573341 H
Protection type	External short-circuit protection External overload protection DC inductive overvoltage protection AC inductive overvoltage protection
Output overload protection	Use 1 fast blow fuse per channel or group of channel
Output overvoltage protection	Use ZNO surge limiter on each output AC Use RC circuit on each output AC Use discharge diode on each output DC
Output short-circuit protection	Use 1 fast blow fuse per channel or group of channel
Minimum switching current	1 mA 5 V DC

Electrical durability	700000 cycles AC-12 50 VA 24 V at -25...60 °C 700000 cycles AC-12 30 VA 24 V at 70 °C 5000000 cycles AC-15 6 VA 48 V 0.35 at 70 °C 500000 cycles AC-15 24 VA 24 V 0.35 at -25...60 °C 500000 cycles AC-15 14.4 VA 24 V 0.35 at 70 °C 500000 cycles AC-15 10 VA 48 V 0.35 at -25...60 °C 500000 cycles AC-12 66 VA 48 V at 70 °C 500000 cycles AC-12 220 VA 110...120 V at -25...60 °C 500000 cycles AC-12 132 VA 110...120 V at 70 °C 500000 cycles AC-12 110 VA 48 V at -25...60 °C 3000000 cycles AC-15 50 VA 200...240 V 0.35 at -25...60 °C 3000000 cycles AC-15 30 VA 200...240 V at 70 °C 300000 cycles DC-12 40 W 24 V at -25...60 °C 300000 cycles DC-12 24 VA 24 V at 70 °C 2000000 cycles DC-13 6 VA 24 V at 70 °C 2000000 cycles DC-13 10 W 24 V at -25...60 °C 2000000 cycles AC-15 24 VA 48 V 0.35 at -25...60 °C 2000000 cycles AC-15 14.4 VA 48 V 0.35 at 70 °C 1500000 cycles AC-15 50 VA 110...120 V 0.35 at -25...60 °C 1500000 cycles AC-15 30 VA 110...120 V 0.35 at 70 °C 150000 cycles AC-15 60 VA 110...120 V 0.35 at 70 °C 150000 cycles AC-15 110 VA 110...120 V 0.35 at -25...60 °C 10000000 cycles AC-15 6 VA 200...240 V at 70 °C 10000000 cycles AC-15 6 VA 110...120 V 0.35 at 70 °C 10000000 cycles AC-15 10 VA 200...240 V 0.35 at -25...60 °C 10000000 cycles AC-15 10 VA 110...120 V 0.35 at -25...60 °C 1000000 cycles DC-13 24 W 24 V at -25...60 °C 1000000 cycles DC-13 14.4 VA 24 V at 70 °C 1000000 cycles DC-12 24 W 24 V at -25...60 °C 1000000 cycles DC-12 14.4 VA 24 V at 70 °C 1000000 cycles AC-15 60 VA 200...240 V at 70 °C 1000000 cycles AC-15 110 VA 200...240 V 0.35 at -25...60 °C 1000000 cycles AC-12 66 VA 110...120 V at 70 °C 1000000 cycles AC-12 50 VA 48 V at -25...60 °C 1000000 cycles AC-12 30 VA 48 V at 70 °C 1000000 cycles AC-12 220 VA 200...240 V at -25...60 °C 1000000 cycles AC-12 132 VA 200...240 V at 70 °C 1000000 cycles AC-12 110 VA 110...120 V at -25...60 °C 100000 cycles AC-15 220 VA 200...240 V 0.35 at -25...60 °C 100000 cycles AC-15 132 VA 200...240 V at 70 °C
Status LED	1 LED red for module I/O 1 LED red for module error (ERR) 1 LED per channel green for channel diagnostic 1 LED green for module operating (RUN)
Product weight	0.145 kg

Environment


IP degree of protection	IP20
Standards	CSA C22.2 No 142 IEC 1131-2 IEC 664 NF C 63-850 UL 508 UL 746C
Dielectric strength	2000 V AC at 50/60 Hz 1 min
Ambient air temperature for operation	-25...70 °C
Relative humidity	10...95 % without condensation
Protective treatment	Conformal coating Humiseal 1A33 TC
Environmental characteristic	3C4 conforming to EN/IEC 60721-3-3 3C3 conforming to EN/IEC 60721-3-3

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental

Modules Mounted on Racks

Dimensions




- (1) With removable terminal block (cage, screw or spring).
- (2) With FCN connector.
- (3) On AM1 ED rail: 35 mm wide, 15 mm deep. Only possible with BMXXBP0400/0400H/0600/0600H/0800/0800H rack.


Rack references	a in mm	a in in.
BMXXBP0400 and BMXXBP0400H	242.4	09.54
BMXXBP0600 and BMXXBP0600H	307.6	12.11
BMXXBP0800 and BMXXBP0800H	372.8	14.68
BMXXBP1200 and BMXXBP1200H	503.2	19.81

Connecting the Module

Output Circuit Diagram



Module Connection



power 24 VDC or 24...240 VAC

supply

fuse 1 fast blow fuse of 3 A for each relay

NC not connected