

# BMXFCA300

cord set - 20-way terminal - SUB-D25  
connector - for M340 I/O - 3 m



## Main

|                                |                                                                                      |
|--------------------------------|--------------------------------------------------------------------------------------|
| Range of product               | Modicon M340 automation platform                                                     |
| Accessory / separate part type | Preformed cordset                                                                    |
| Product compatibility          | ABE7CPA02<br>ABE7CPA410<br>BMXAMI0410<br>BMXAMO0802                                  |
| Electrical connection          | 1 removable terminal block 20 ways module side<br>1 connector SUB-D 25 sub-base side |
| Cable length                   | 3 m                                                                                  |

## Complementary

|                |        |
|----------------|--------|
| Product weight | 0.5 kg |
|----------------|--------|

## Offer Sustainability

|                                  |                                                                                          |
|----------------------------------|------------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                    |
| RoHS (date code: YYWW)           | Compliant - since 1001 - <a href="#">Schneider Electric declaration of conformity</a>    |
| REACH                            | Reference contains SVHC above the threshold - <a href="#">go to CaP for more details</a> |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                                 |
| Product end of life instructions | Need no specific recycling operations                                                    |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.