

# BRH0571P00F1A

AC servo motors BRH - 0.46 N.m - 6000 rpm -  
untapped shaft - with brake - IP41

## Main

|                             |                                                                                                                                                  |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Product or component type   | Motion servo motors                                                                                                                              |
| Component name              | BRH                                                                                                                                              |
| Continuous stall torque     | 0.46 N.m                                                                                                                                         |
| Peak stall torque           | 1.26 N.m for LXM05CU70M2<br>1.39 N.m for LXM05AD14N4<br>1.39 N.m for LXM05BD14N4<br>1.39 N.m for LXM05CD14N4                                     |
| Nominal output power        | 135 W for LXM05CU70M2<br>260 W for LXM05AD14N4<br>260 W for LXM05BD14N4<br>260 W for LXM05CD14N4                                                 |
| Nominal speed               | 3000 rpm for LXM05CU70M2<br>6000 rpm for LXM05AD14N4<br>6000 rpm for LXM05BD14N4<br>6000 rpm for LXM05CD14N4                                     |
| Maximum mechanical speed    | 8000 rpm                                                                                                                                         |
| Product compatibility       | LXM05AD14N4 at 400/480 V 3 phases<br>LXM05BD14N4 at 400/480 V 3 phases<br>LXM05CD14N4 at 400/480 V 3 phases<br>LXM05CU70M2 at 230 V single phase |
| Shaft end                   | Untapped                                                                                                                                         |
| IP degree of protection     | IP41                                                                                                                                             |
| Encoder type                | Single turn SinCos Hiperface                                                                                                                     |
| Encoder feedback resolution | 16384 points/turn                                                                                                                                |
| Holding brake               | With                                                                                                                                             |
| Mounting support            | International standard flange                                                                                                                    |
| Electrical connection       | Straight connectors                                                                                                                              |
| Number of poles             | 10                                                                                                                                               |

## Complementary

|                                 |                                                                                                              |
|---------------------------------|--------------------------------------------------------------------------------------------------------------|
| Range compatibility             | Lexium 05                                                                                                    |
| Switching frequency             | 8 kHz                                                                                                        |
| Nominal torque                  | 0.41 N.m for LXM05AD14N4<br>0.41 N.m for LXM05BD14N4<br>0.41 N.m for LXM05CD14N4<br>0.43 N.m for LXM05CU70M2 |
| Maximum current Irms            | 4.3 A for LXM05CU70M2<br>5.4 A for LXM05CD14N4<br>5.4 A for LXM05BD14N4<br>5.4 A for LXM05AD14N4             |
| Torque constant                 | 0.34 N.m/A rms at 120 °C                                                                                     |
| Back emf constant               | 20.9 V rms/krpm at 120 °C                                                                                    |
| Rotor inertia                   | 0.18 kg.cm <sup>2</sup> with brake<br>0.18 kg.cm <sup>2</sup> without brake                                  |
| Stator resistance               | 12.7 Ohm                                                                                                     |
| Stator inductance               | 24.1 mH                                                                                                      |
| Stator electrical time constant | 1.9 ms                                                                                                       |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                         |                                                                                                                       |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Maximum radial force Fr | 72 N at 6000 rpm<br>73 N at 5000 rpm<br>74 N at 4000 rpm<br>76 N at 3000 rpm<br>81 N at 2000 rpm<br>109 N at 1000 rpm |
| Maximum axial force Fa  | 0.2 x Fr                                                                                                              |
| Product weight          | 1.1 kg                                                                                                                |

## Environment

|                          |                   |
|--------------------------|-------------------|
| RoHS EUR conformity date | 4Q2009            |
| RoHS EUR status          | Will be compliant |