

# BSH0553M01A1A

AC servo motor BSH - 0.9 Nm - 8000 rpm -  
untapped shaft - without brake - IP50

## Main

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product or component type | AC servo motors                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Component name            | BSH                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Continuous stall torque   | 1.3 N.m for LXM15LU60N4 at 400 V 3 phases<br>1.3 N.m for LXM15LU60N4 at 480 V 3 phases<br>1.3 N.m for LXM05AD10M2 at 200...240 V single phase<br>1.3 N.m for LXM05AD10M3X at 200...240 V 3 phases<br>1.3 N.m for LXM05BD10M2 at 200...240 V single phase<br>1.3 N.m for LXM05BD10M3X at 200...240 V 3 phases<br>1.3 N.m for LXM05CD10M2 at 200...240 V single phase<br>1.3 N.m for LXM05CD10M3X at 200...240 V 3 phases         |
| Peak stall torque         | 3.5 N.m for LXM15LU60N4 at 400 V 3 phases<br>3.5 N.m for LXM15LU60N4 at 480 V 3 phases<br>3.5 N.m for LXM05AD10M2 at 200...240 V single phase<br>3.5 N.m for LXM05AD10M3X at 200...240 V 3 phases<br>3.5 N.m for LXM05BD10M2 at 200...240 V single phase<br>3.5 N.m for LXM05BD10M3X at 200...240 V 3 phases<br>3.5 N.m for LXM05CD10M2 at 200...240 V single phase<br>3.5 N.m for LXM05CD10M3X at 200...240 V 3 phases         |
| Nominal output power      | 190 W for LXM05AD10M2 at 200...240 V single phase<br>190 W for LXM05AD10M3X at 200...240 V 3 phases<br>190 W for LXM05BD10M2 at 200...240 V single phase<br>190 W for LXM05BD10M3X at 200...240 V 3 phases<br>190 W for LXM05CD10M2 at 200...240 V single phase<br>190 W for LXM05CD10M3X at 200...240 V 3 phases<br>460 W for LXM15LU60N4 at 400 V 3 phases<br>524 W for LXM15LU60N4 at 480 V 3 phases                         |
| Nominal speed             | 1500 rpm for LXM05AD10M2 at 200...240 V single phase<br>1500 rpm for LXM05AD10M3X at 200...240 V 3 phases<br>1500 rpm for LXM05BD10M2 at 200...240 V single phase<br>1500 rpm for LXM05BD10M3X at 200...240 V 3 phases<br>1500 rpm for LXM05CD10M2 at 200...240 V single phase<br>1500 rpm for LXM05CD10M3X at 200...240 V 3 phases<br>4000 rpm for LXM15LU60N4 at 400 V 3 phases<br>5000 rpm for LXM15LU60N4 at 480 V 3 phases |
| Maximum mechanical speed  | 8000 rpm                                                                                                                                                                                                                                                                                                                                                                                                                        |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                             |                                                                                                                                                                                                                                                                                                                         |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product compatibility       | LXM05AD10M2 at 200...240 V single phase<br>LXM05AD10M3X at 200...240 V 3 phases<br>LXM05BD10M2 at 200...240 V single phase<br>LXM05BD10M3X at 200...240 V 3 phases<br>LXM05CD10M2 at 200...240 V single phase<br>LXM05CD10M3X at 200...240 V 3 phases<br>LXM15LU60N4 at 400 V 3 phases<br>LXM15LU60N4 at 480 V 3 phases |
| Shaft end                   | Untapped                                                                                                                                                                                                                                                                                                                |
| IP degree of protection     | IP50                                                                                                                                                                                                                                                                                                                    |
| Encoder type                | Absolute single turn SinCos Hiperface                                                                                                                                                                                                                                                                                   |
| Encoder feedback resolution | 131072 points/turn                                                                                                                                                                                                                                                                                                      |
| Holding brake               | Without                                                                                                                                                                                                                                                                                                                 |
| Mounting support            | International standard flange                                                                                                                                                                                                                                                                                           |
| Electrical connection       | Straight connectors                                                                                                                                                                                                                                                                                                     |
| Number of poles             | 6                                                                                                                                                                                                                                                                                                                       |

## Complementary

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range compatibility                         | Lexium 05<br>Lexium 15                                                                                                                                                                                                                                                                                                                                                                                                  |
| Nominal torque                              | 1.1 N.m for LXM15LU60N4 at 400 V 3 phases<br>1.1 N.m for LXM15LU60N4 at 480 V 3 phases<br>1.2 N.m for LXM05AD10M2 at 200...240 V single phase<br>1.2 N.m for LXM05AD10M3X at 200...240 V 3 phases<br>1.2 N.m for LXM05BD10M2 at 200...240 V single phase<br>1.2 N.m for LXM05BD10M3X at 200...240 V 3 phases<br>1.2 N.m for LXM05CD10M2 at 200...240 V single phase<br>1.2 N.m for LXM05CD10M3X at 200...240 V 3 phases |
| Maximum current Irms                        | 3.4 A for LXM05CD10M3X<br>3.4 A for LXM05AD10M2<br>3.4 A for LXM05AD10M3X<br>3.4 A for LXM05BD10M2<br>3.4 A for LXM05BD10M3X<br>3.4 A for LXM05CD10M2<br>3.6 A for LXM15LU60N4                                                                                                                                                                                                                                          |
| Switching frequency                         | 4 kHz for LEX05                                                                                                                                                                                                                                                                                                                                                                                                         |
| Torque constant                             | 1.18 N.m/A rms at 120 °C<br>1.33 N.m/A rms at 120 °C                                                                                                                                                                                                                                                                                                                                                                    |
| Back electromagnetical force (emf) constant | 78 V rms/krpm at 120 °C<br>79 V rms/krpm at 120 °C                                                                                                                                                                                                                                                                                                                                                                      |
| Rotor inertia                               | 0.19 kg.cm <sup>2</sup> without brake                                                                                                                                                                                                                                                                                                                                                                                   |
| Stator resistance                           | 32 Ohm at 20 °C<br>38.4 Ohm at 20 °C                                                                                                                                                                                                                                                                                                                                                                                    |
| Stator inductance                           | 48 mH at 20 °C<br>92.2 mH at 20 °C                                                                                                                                                                                                                                                                                                                                                                                      |
| Stator electrical time constant             | 1.5 ms at 20 °C<br>2.4 ms at 20 °C                                                                                                                                                                                                                                                                                                                                                                                      |
| Maximum radial force Fr                     | 190 N at 8000 rpm<br>200 N at 7000 rpm<br>210 N at 6000 rpm<br>230 N at 5000 rpm<br>240 N at 4000 rpm<br>270 N at 3000 rpm<br>310 N at 2000 rpm<br>390 N at 1000 rpm                                                                                                                                                                                                                                                    |
| Maximum axial force Fa                      | 0.2 x Fr                                                                                                                                                                                                                                                                                                                                                                                                                |
| Product weight                              | 1.76 kg                                                                                                                                                                                                                                                                                                                                                                                                                 |

## Environment

|                          |           |
|--------------------------|-----------|
| RoHS EUR conformity date | 0850      |
| RoHS EUR status          | Compliant |