

BSH0553T11A1A

AC servo motor BSH - 1.3 Nm - 9000 rpm - key
shaft - without brake - IP50

Main

Product or component type	AC servo motors
Component name	BSH
Continuous stall torque	1.3 N.m for LXM05AD17F1 at 110...120 V single phase 1.3 N.m for LXM05AD17M2 at 200...240 V single phase 1.3 N.m for LXM05AD17M3X at 200...240 V 3 phases 1.3 N.m for LXM05BD17F1 at 110...120 V single phase 1.3 N.m for LXM05BD17M2 at 200...240 V single phase 1.3 N.m for LXM05BD17M3X at 200...240 V 3 phases 1.3 N.m for LXM05CD17F1 at 110...120 V single phase 1.3 N.m for LXM05CD17M2 at 200...240 V single phase 1.3 N.m for LXM05CD17M3X at 200...240 V 3 phases
Peak stall torque	3.31 N.m for LXM05AD17F1 at 110...120 V single phase 3.31 N.m for LXM05AD17M2 at 200...240 V single phase 3.31 N.m for LXM05AD17M3X at 200...240 V 3 phases 3.31 N.m for LXM05BD17F1 at 110...120 V single phase 3.31 N.m for LXM05BD17M2 at 200...240 V single phase 3.31 N.m for LXM05BD17M3X at 200...240 V 3 phases 3.31 N.m for LXM05CD17F1 at 110...120 V single phase 3.31 N.m for LXM05CD17M2 at 200...240 V single phase 3.31 N.m for LXM05CD17M3X at 200...240 V 3 phases
Nominal output power	350 W for LXM05AD17F1 at 110...120 V single phase 350 W for LXM05AD17M2 at 200...240 V single phase 350 W for LXM05AD17M3X at 200...240 V 3 phases 350 W for LXM05BD17F1 at 110...120 V single phase 350 W for LXM05BD17M2 at 200...240 V single phase 350 W for LXM05BD17M3X at 200...240 V 3 phases 350 W for LXM05CD17F1 at 110...120 V single phase 350 W for LXM05CD17M2 at 200...240 V single phase 350 W for LXM05CD17M3X at 200...240 V 3 phases

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Nominal speed	3000 rpm for LXM05AD17F1 at 110...120 V single phase 3000 rpm for LXM05AD17M2 at 200...240 V single phase 3000 rpm for LXM05AD17M3X at 200...240 V 3 phases 3000 rpm for LXM05BD17F1 at 110...120 V single phase 3000 rpm for LXM05BD17M2 at 200...240 V single phase 3000 rpm for LXM05BD17M3X at 200...240 V 3 phases 3000 rpm for LXM05CD17F1 at 110...120 V single phase 3000 rpm for LXM05CD17M2 at 200...240 V single phase 3000 rpm for LXM05CD17M3X at 200...240 V 3 phases
Maximum mechanical speed	9000 rpm
Product compatibility	LXM05AD17F1 at 110...120 V single phase LXM05AD17M2 at 200...240 V single phase LXM05AD17M3X at 200...240 V 3 phases LXM05BD17F1 at 110...120 V single phase LXM05BD17M2 at 200...240 V single phase LXM05BD17M3X at 200...240 V 3 phases LXM05CD17F1 at 110...120 V single phase LXM05CD17M2 at 200...240 V single phase LXM05CD17M3X at 200...240 V 3 phases
Shaft end	Keyed
IP degree of protection	IP50
Encoder type	Absolute single turn SinCos Hiperface
Encoder feedback resolution	131072 points/turn
Holding brake	Without
Mounting support	International standard flange
Electrical connection	Straight connectors
Number of poles	6

Complementary

Range compatibility	Lexium 05
Nominal torque	1.1 N.m for LXM05AD17F1 at 110...120 V single phase 1.1 N.m for LXM05AD17M2 at 200...240 V single phase 1.1 N.m for LXM05AD17M3X at 200...240 V 3 phases 1.1 N.m for LXM05BD17F1 at 110...120 V single phase 1.1 N.m for LXM05BD17M2 at 200...240 V single phase 1.1 N.m for LXM05BD17M3X at 200...240 V 3 phases 1.1 N.m for LXM05CD17F1 at 110...120 V single phase 1.1 N.m for LXM05CD17M2 at 200...240 V single phase 1.1 N.m for LXM05CD17M3X at 200...240 V 3 phases
Maximum current Irms	11.9 A for LXM05AD17F1 11.9 A for LXM05AD17M2 11.9 A for LXM05AD17M3X 11.9 A for LXM05BD17F1 11.9 A for LXM05BD17M2 11.9 A for LXM05BD17M3X 11.9 A for LXM05CD17F1 11.9 A for LXM05CD17M2 11.9 A for LXM05CD17M3X
Switching frequency	8 kHz for LEX05
Torque constant	0.39 N.m/A rms at 120 °C
Back electromagnetical force (emf) constant	22 V rms/krpm at 120 °C
Rotor inertia	0.134 kg.cm ² without brake
Stator resistance	3.1 Ohm at 20 °C
Stator inductance	7.4 mH at 20 °C
Stator electrical time constant	2.39 ms at 20 °C

Maximum radial force Fr	190 N at 8000 rpm
	200 N at 7000 rpm
	210 N at 6000 rpm
	230 N at 5000 rpm
	240 N at 4000 rpm
	270 N at 3000 rpm
	310 N at 2000 rpm
	390 N at 1000 rpm
Maximum axial force Fa	0.2 x Fr
Product weight	1.76 kg

Environment

RoHS EUR conformity date	0850
RoHS EUR status	Compliant