

BSH0701M02F1A

AC servo motor BSH - 1.4 Nm - 8000 rpm -
untapped shaft - with brake - IP50

Main

Product or component type	AC servo motors
Component name	BSH
Continuous stall torque	1.4 N.m for LXM05AD10M3X at 200...240 V 3 phases 1.4 N.m for LXM05BD10M3X at 200...240 V 3 phases 1.4 N.m for LXM05CD10M3X at 200...240 V 3 phases
Peak stall torque	2.66 N.m for LXM05AD10M3X at 200...240 V 3 phases 2.66 N.m for LXM05BD10M3X at 200...240 V 3 phases 2.66 N.m for LXM05CD10M3X at 200...240 V 3 phases
Nominal output power	210 W for LXM05AD10M3X at 200...240 V 3 phases 210 W for LXM05BD10M3X at 200...240 V 3 phases 210 W for LXM05CD10M3X at 200...240 V 3 phases
Nominal speed	1500 rpm for LXM05AD10M3X at 200...240 V 3 phases 1500 rpm for LXM05BD10M3X at 200...240 V 3 phases 1500 rpm for LXM05CD10M3X at 200...240 V 3 phases
Maximum mechanical speed	8000 rpm
Product compatibility	LXM05AD10M3X at 200...240 V 3 phases LXM05BD10M3X at 200...240 V 3 phases LXM05CD10M3X at 200...240 V 3 phases
Shaft end	Untapped
IP degree of protection	IP50
Encoder type	Absolute multitrans SinCos Hiperface
Encoder feedback resolution	131072 points/turn x 4096 turns
Holding brake	With
Mounting support	International standard flange
Electrical connection	Straight connectors
Number of poles	6

Complementary

Range compatibility	Lexium 05
Nominal torque	1.36 N.m for LXM05AD10M3X at 200...240 V 3 phases 1.36 N.m for LXM05BD10M3X at 200...240 V 3 phases 1.36 N.m for LXM05CD10M3X at 200...240 V 3 phases
Maximum current Irms	3.1 A for LXM05AD10M3X 3.1 A for LXM05BD10M3X 3.1 A for LXM05CD10M3X
Switching frequency	4 kHz for LEX05
Torque constant	1.4 N.m/A rms at 120 °C
Back electromagnetical force (emf) constant	85 V rms/krpm at 120 °C
Rotor inertia	0.322 kg.cm² with brake
Stator resistance	35.4 Ohm at 20 °C
Stator inductance	131.9 mH at 20 °C
Stator electrical time constant	3.73 ms at 20 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Maximum radial force Fr	360 N at 6000 rpm 380 N at 5000 rpm 410 N at 4000 rpm 460 N at 3000 rpm 520 N at 2000 rpm 660 N at 1000 rpm
Maximum axial force Fa	0.2 x Fr
Product weight	2.2 kg

Environment

RoHS EUR conformity date	0850
RoHS EUR status	Compliant