

BSH1002P11A2A

AC servo motor BSH - 5.5 Nm - 6000 rpm - key
shaft - without brake - IP50

Main

Product or component type	AC servo motors
Component name	BSH
Continuous stall torque	3.4 N.m for LXM15LD13M3 at 230 V 3 phases 3.4 N.m for LXM15LD10N4 at 230 V 3 phases 3.4 N.m for LXM15LD10N4 at 400 V 3 phases 3.4 N.m for LXM15LD10N4 at 480 V 3 phases 4.5 N.m for LXM15LD21M3 at 230 V single phase 5.5 N.m for LXM05AD17M3X at 200...240 V 3 phases 5.5 N.m for LXM05AD22N4 at 380...480 V 3 phases 5.5 N.m for LXM05AD28M2 at 200...240 V single phase 5.5 N.m for LXM05BD17M3X at 200...240 V 3 phases 5.5 N.m for LXM05BD22N4 at 380...480 V 3 phases 5.5 N.m for LXM05BD28M2 at 200...240 V single phase 5.5 N.m for LXM05CD17M3X at 200...240 V 3 phases 5.5 N.m for LXM05CD22N4 at 380...480 V 3 phases 5.5 N.m for LXM05CD28M2 at 200...240 V single phase 5.8 N.m for LXM15LD17N4 at 400 V 3 phases 5.8 N.m for LXM15LD17N4 at 480 V 3 phases 5.8 N.m for LXM15LD21M3 at 230 V 3 phases
Peak stall torque	5.6 N.m for LXM15LD13M3 at 230 V 3 phases 8 N.m for LXM15LD10N4 at 230 V 3 phases 8 N.m for LXM15LD10N4 at 400 V 3 phases 8 N.m for LXM15LD10N4 at 480 V 3 phases 9.39 N.m for LXM15LD21M3 at 230 V single phase 11.23 N.m for LXM05AD17M3X at 200...240 V 3 phases 11.23 N.m for LXM05BD17M3X at 200...240 V 3 phases 11.23 N.m for LXM05CD17M3X at 200...240 V 3 phases 12.13 N.m for LXM15LD17N4 at 400 V 3 phases 12.13 N.m for LXM15LD17N4 at 480 V 3 phases 13.92 N.m for LXM05AD22N4 at 380...480 V 3 phases 13.92 N.m for LXM05BD22N4 at 380...480 V 3 phases 13.92 N.m for LXM05CD22N4 at 380...480 V 3 phases 14.79 N.m for LXM15LD21M3 at 230 V 3 phases 16 N.m for LXM05AD28M2 at 200...240 V single phase 16 N.m for LXM05BD28M2 at 200...240 V single phase 16 N.m for LXM05CD28M2 at 200...240 V single phase
Nominal output power	780 W for LXM05AD17M3X at 200...240 V 3 phases 780 W for LXM05AD28M2 at 200...240 V single phase 780 W for LXM05BD17M3X at 200...240 V 3 phases 780 W for LXM05BD28M2 at 200...240 V single phase 780 W for LXM05CD17M3X at 200...240 V 3 phases 780 W for LXM05CD28M2 at 200...240 V single phase 840 W for LXM15LD13M3 at 230 V 3 phases 890 W for LXM15LD10N4 at 230 V 3 phases 950 W for LXM15LD21M3 at 230 V single phase 950 W for LXM15LD21M3 at 230 V 3 phases 1400 W for LXM05AD22N4 at 380...480 V 3 phases 1400 W for LXM05BD22N4 at 380...480 V 3 phases 1400 W for LXM05CD22N4 at 380...480 V 3 phases 1600 W for LXM15LD10N4 at 400 V 3 phases 1700 W for LXM15LD17N4 at 400 V 3 phases 1950 W for LXM15LD17N4 at 480 V 3 phases 2150 W for LXM15LD10N4 at 480 V 3 phases

Nominal speed	1500 rpm for LXM05AD17M3X at 200...240 V 3 phases 1500 rpm for LXM05AD28M2 at 200...240 V single phase 1500 rpm for LXM05BD17M3X at 200...240 V 3 phases 1500 rpm for LXM05BD28M2 at 200...240 V single phase 1500 rpm for LXM05CD17M3X at 200...240 V 3 phases 1500 rpm for LXM05CD28M2 at 200...240 V single phase 2000 rpm for LXM15LD21M3 at 230 V single phase 2000 rpm for LXM15LD21M3 at 230 V 3 phases 2500 rpm for LXM15LD13M3 at 230 V 3 phases 2500 rpm for LXM15LD10N4 at 230 V 3 phases 3000 rpm for LXM05AD22N4 at 380...480 V 3 phases 3000 rpm for LXM05BD22N4 at 380...480 V 3 phases 3000 rpm for LXM05CD22N4 at 380...480 V 3 phases 4000 rpm for LXM15LD17N4 at 400 V 3 phases 4500 rpm for LXM15LD10N4 at 400 V 3 phases 5000 rpm for LXM15LD17N4 at 480 V 3 phases 6000 rpm for LXM15LD10N4 at 480 V 3 phases
Maximum mechanical speed	6000 rpm
Product compatibility	LXM05AD17M3X at 200...240 V 3 phases LXM05AD22N4 at 380...480 V 3 phases LXM05AD28M2 at 200...240 V single phase LXM05BD17M3X at 200...240 V 3 phases LXM05BD22N4 at 380...480 V 3 phases LXM05BD28M2 at 200...240 V single phase LXM05CD17M3X at 200...240 V 3 phases LXM05CD22N4 at 380...480 V 3 phases LXM05CD28M2 at 200...240 V single phase LXM15LD10N4 at 230 V 3 phases LXM15LD10N4 at 400 V 3 phases LXM15LD10N4 at 480 V 3 phases LXM15LD13M3 at 230 V 3 phases LXM15LD17N4 at 400 V 3 phases LXM15LD17N4 at 480 V 3 phases LXM15LD21M3 at 230 V single phase LXM15LD21M3 at 230 V 3 phases
Shaft end	Keyed
IP degree of protection	IP50
Encoder type	Absolute single turn SinCos Hiperface
Encoder feedback resolution	131072 points/turn
Holding brake	Without
Mounting support	International standard flange
Electrical connection	Rotatable right-angled connectors
Number of poles	8

Complementary

Range compatibility	Lexium 05 Lexium 15
Nominal torque	3.4 N.m for LXM15LD10N4 at 230 V 3 phases 3.4 N.m for LXM15LD10N4 at 400 V 3 phases 3.4 N.m for LXM15LD10N4 at 480 V 3 phases 3.4 N.m for LXM15LD13M3 at 230 V 3 phases 3.7 N.m for LXM15LD17N4 at 480 V 3 phases 4 N.m for LXM15LD17N4 at 400 V 3 phases 4.4 N.m for LXM05AD22N4 at 380...480 V 3 phases 4.4 N.m for LXM05BD22N4 at 380...480 V 3 phases 4.4 N.m for LXM05CD22N4 at 380...480 V 3 phases 4.5 N.m for LXM15LD21M3 at 230 V single phase 4.96 N.m for LXM05AD28M2 at 200...240 V single phase 4.96 N.m for LXM05AD17M3X at 200...240 V 3 phases 4.96 N.m for LXM05BD28M2 at 200...240 V single phase 4.96 N.m for LXM05BD17M3X at 200...240 V 3 phases 4.96 N.m for LXM05CD28M2 at 200...240 V single phase 4.96 N.m for LXM05CD17M3X at 200...240 V 3 phases 5.8 N.m for LXM15LD21M3 at 230 V 3 phases
Maximum current I _{rms}	17.1 A for LXM15LD13M3 17.1 A for LXM15LD21M3 17.1 A for LXM15LD10N4 17.1 A for LXM15LD17N4 17.1 A for LXM05AD28M2 17.1 A for LXM05AD17M3X 17.1 A for LXM05AD22N4 17.1 A for LXM05BD28M2 17.1 A for LXM05BD17M3X 17.1 A for LXM05BD22N4 17.1 A for LXM05CD28M2 17.1 A for LXM05CD17M3X 17.1 A for LXM05CD22N4
Switching frequency	8 kHz for LEX05
Torque constant	1.21 N.m/A rms at 120 °C
Back electromagnetical force (emf) constant	77 V rms/krpm at 120 °C
Rotor inertia	2.31 kg.cm ² without brake
Stator resistance	2.4 Ohm at 20 °C
Stator inductance	12.7 mH at 20 °C 13.5 mH at 20 °C
Stator electrical time constant	5.29 ms at 20 °C 5.63 ms at 20 °C
Maximum radial force Fr	620 N at 4000 rpm 690 N at 3000 rpm 790 N at 2000 rpm 990 N at 1000 rpm
Maximum axial force Fa	0.2 x Fr
Product weight	5.9 kg

Environment

RoHS EUR conformity date	0850
RoHS EUR status	Compliant