

BD2-AK3X/GS00 TAP-OFF UNIT 125A / 1X 3POLE FU
SE SOCKET GS00

Model		
Product designation		tap-off unit for BD2 busbar trunking system
Protection class		
Protection class IP		IP54
Main circuit		
Operating frequency / rated value		
• minimum	Hz	50
• maximum	Hz	60
Operating voltage / at AC		
• at 50 Hz / rated value / maximum	V	690
• at 60 Hz / rated value / maximum	V	690
Operating current		
• for circuit 1 / at AC / at 50 Hz / rated value / maximum	A	125
• for circuit 1 / at AC / at 60 Hz / rated value / maximum	A	125
Connections		
Connectable conductor cross-section / in the outgoing unit		
• minimum	mm ²	10
• maximum	mm ²	70
Tap-off points		
Outgoing unit version		cable entry
Design of short-circuit and overloading protection / in the outgoing unit		3-pole NH00 125 A fuse base
Size of the outgoing feeder		3
Number of poles / of the outgoing feeder		5
Mechanical Design		
Height	mm	160
Width	mm	205
Length	mm	440
Product component / Locking mechanism		Yes

Declaration of Conformity



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/BVP:203162>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/BVP:203162/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=BVP:203162

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

29.06.2016