

+BD01-GK-BL-EIB ANCILL.EQUIPM.UNIT LIGHTING
CONTROL EIB

General technical details:

Product-type designation		+BD01-GK-BL-EIB
Product designation		ancillary equipment unit for BD01 busbar trunking system
Product function / phase selection		No
Operating voltage		
• at 50 Hz / at AC / rated value / maximum	V	400
• at 60 Hz / at AC / rated value / maximum	V	400
Number of CEE sockets		0
Number of safety sockets		0

Mechanical design:

Product component		
• locking		Yes
• outgoing unit for mounting in devices		No
Length	mm	245
Width	mm	160
Height	mm	130
Color		light grey
RAL color number		RAL 7035

Outgoing unit:

Design of the outgoing unit		cable entry
-----------------------------	--	-------------

Ambient conditions:

Protection class IP		IP54
---------------------	--	------

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Global Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/BVP:257125/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=BVP:257125

last change:

Sep 3, 2012