
SIEMENS

Product data sheet BVP:261750

BD2C-3-1250-SB-2 STANDARD LENGTH 2,25M 1250A, N + PE, 8 TAP OFFS



Similar to image

General technical details:			
Product designation		trunking unit for BD2 busbar trunking system	
Product-type designation		BD2C-3-1250-SB-2	
Operating current			
• for circuit 1 / at 50 Hz / for AC / rated value / maximum	Α	1,250	
• for circuit 1 / at 60 Hz / for AC / rated value / maximum	Α	1,250	
Resistance against the impulse current / at 690 V / rated value	kA	90	
Short-time current resistance (lcw) / at 690 V			
• limited to 1 s / rated value	kA	34	
• limited to 0.1 s / rated value	kA	43	
Operating frequency / rated value			
• minimum	Hz	50	
• maximum	Hz	60	
Operating voltage			
• at 50 Hz / at AC / rated value / maximum	V	690	
• at 60 Hz / at AC / rated value / maximum	V	690	
Insulation voltage			
• for AC / rated value	V	690	
• for DC / rated value	V	800	

Number of conductors		5		
• without PE		4		
Product component / fire sealing		No		
Mechanical design:				
Conductor cross section / of the (PE)N	mm²	699		
Mounting type		ceiling / wall		
Width	mm	167		
Height	mm	126		
Color		light grey		
Busbar:				
Configuration of the busbars		L1,L2,L3,N		
Material / of the busbar		copper		
Busway section:				
Length / of the busbar box	m	2.25		
mounting position / of the busbar box		horizontal edgewise, horizontal flat, vertical		
Number of circuits / in one busbar box		1		
Outgoing openings:				
Outgoing point distance	m	0.5		
Number of the outgoing points / maximum		8		
Arrangement of the outgoing points		on both sides		
Ambient conditions:				
Protection class IP		IP52		
Further information:				
Information- and Downloadcenter (Catalogs, Brochures,) http://www.siemens.com/lowvoltage/catalogs				
Global Industry Mall (Online ordering system) http://www.siemens.com/lowvoltage/mall				
Service&Support (Manuals, Certificates, Characteristics, FAQs,) http://support.automation.siemens.com/WW/view/en/BVP:261750/all				
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams,) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=BVP:261750				

last change: Jul 7, 2014