


BD2-AK05/LSD-EC400-N TAP-OFF UNIT 400A / 1X 4 POLE
WITH CIRCUITBREAKER 3VL4740 ROTARY DRIVE



Similar to image

General technical details:		
Product designation		tap-off unit for BD2 busbar trunking system
Product-type designation		BD2-AK05/LSD-EC400-N
Product function / phase selection		No
Operating current - for circuit 1 - at 50 Hz / for AC / rated value / maximum - at 60 Hz / for AC / rated value / maximum	A A	400 400
Operating frequency rated value	Hz	50 ... 60
Operating voltage - at 50 Hz / at AC / rated value / maximum - at 60 Hz / at AC / rated value / maximum	V V	400 400
Number of CEE sockets		0
Number of safety sockets		0
Mechanical design:		
Product component / locking		Yes
Length	mm	924
Width	mm	494

Height	mm	408
Color		light grey
RAL color number		RAL 7035
Product component / outgoing unit for mounting in devices		No
Conductor cross section that can be connected • in the outgoing unit	mm ²	10 ... 120

Outgoing unit:

Design of the outgoing unit		cable entry
Execution of short-circuit and overloading protection / in the outgoing unit		4-pole 400 A circuit-breaker with rotary drive
Size of the outgoing feeder		05
Number of poles / of the outgoing feeder		5

Ambient conditions:

Protection class IP		IP54
----------------------------	--	------

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Global Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/BVP:610444/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=BVP:610444

last change:

Jul 7, 2014