

# CA3KN227BD3

TeSys K control relay - 2 NO + 2 NC - ≤ 690 V - 24 V DC standard coil



## Main

|                                |                  |
|--------------------------------|------------------|
| Range                          | TeSys            |
| Product name                   | TeSys CAK        |
| Product or component type      | Control relay    |
| Device short name              | CA3K             |
| Contactor application          | Control circuit  |
| Utilisation category           | AC-15<br>DC-13   |
| Pole contact composition       | 2 NO + 2 NC      |
| [Ue] rated operational voltage | ≤ 690 V ≤ 400 Hz |
| Control circuit type           | DC standard      |
| Control circuit voltage        | 24 V DC          |

## Complementary

|                                             |                                                                                                                                                                                      |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Coil technology                             | Built-in bidirectional peak limiting diode suppressor                                                                                                                                |
| [Ith] conventional free air thermal current | 10 A at ≤ 50 °C                                                                                                                                                                      |
| Irms rated making capacity                  | 110 A conforming to IEC 60947                                                                                                                                                        |
| Associated fuse rating                      | 10 A gG conforming to VDE 0660<br>10 A gG conforming to IEC 60947                                                                                                                    |
| [Ui] rated insulation voltage               | 600 V conforming to CSA C22.2 No 14<br>690 V conforming to BS 5424<br>750 V conforming to VDE 0110 group C<br>690 V conforming to IEC 60947                                          |
| Mounting support                            | Plate<br>Rail                                                                                                                                                                        |
| Connections - terminals                     | Faston terminals 2 2.8 mm<br>Faston terminals 1 6.35 mm                                                                                                                              |
| Control circuit voltage limits              | 0.1...0.75 Uc at 50 °C drop-out<br>0.8...1.15 Uc at 50 °C operational                                                                                                                |
| Operating time                              | 25...35 ms coil energisation and NC opening<br>15 ms coil de-energisation and NC closing<br>30...40 ms coil energisation and NO closing<br>10 ms coil de-energisation and NO opening |
| Mechanical durability                       | 20 Mcycles                                                                                                                                                                           |
| Operating rate                              | 10000 cyc/h                                                                                                                                                                          |
| Immunity to microbreaks                     | 2 ms                                                                                                                                                                                 |
| Inrush power in W                           | 3 W at 20 °C                                                                                                                                                                         |
| Hold-in power consumption in W              | 3 W at 20 °C                                                                                                                                                                         |
| Heat dissipation                            | 3 W                                                                                                                                                                                  |
| Minimum switching voltage                   | 17 V                                                                                                                                                                                 |
| Minimum switching current                   | 5 mA                                                                                                                                                                                 |
| Non overlap distance                        | 0.5 mm                                                                                                                                                                               |
| Insulation resistance                       | > 10 MOhm                                                                                                                                                                            |
| Height                                      | 58 mm                                                                                                                                                                                |
| Width                                       | 45 mm                                                                                                                                                                                |
| Depth                                       | 57 mm                                                                                                                                                                                |
| Product weight                              | 0.225 kg                                                                                                                                                                             |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |                                                                                                                                                                                                                                          |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                             | BS 5424<br>IEC 60947<br>NF C 63-140<br>VDE 0660                                                                                                                                                                                          |
| Product certifications                | CSA<br>UL                                                                                                                                                                                                                                |
| Protective treatment                  | TC conforming to IEC 60068                                                                                                                                                                                                               |
| Ambient air temperature for operation | -25...50 °C                                                                                                                                                                                                                              |
| Ambient air temperature for storage   | -50...80 °C                                                                                                                                                                                                                              |
| Operating altitude                    | 2000 m without derating in temperature                                                                                                                                                                                                   |
| Flame retardance                      | Requirement 2 conforming to NF F 16-102<br>Requirement 2 conforming to NF F 16-101<br>V1 conforming to UL 94                                                                                                                             |
| Mechanical robustness                 | Shocks contactor closed 15 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor open 10 Gn for 11 ms IEC 60068-2-27<br>Vibrations contactor closed 4 Gn, 5...300 Hz IEC 60068-2-6<br>Vibrations contactor open 2 Gn, 5...300 Hz IEC 60068-2-6 |