

Product data sheet

Characteristics

CAD323EL

TeSys D control relay - 3 NO + 2 NC - <= 690

V - 48 V DC low consumption coil

Main

Range	TeSys
Product name	TeSys CAD
Product or component type	Control relay
Device short name	CAD
Contactor application	Control circuit
Utilisation category	AC-14 AC-15 DC-13
Pole contact composition	3 NO + 2 NC
[Ue] rated operational voltage	<= 690 V AC 25...400 Hz
Control circuit type	DC low consumption
Control circuit voltage	48 V DC

Complementary

[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
[Ith] conventional free air thermal current	10 A at <= 60 °C
Irms rated making capacity	250 A DC conforming to IEC 60947-5-1 140 A AC conforming to IEC 60947-5-1
[Icw] rated short-time withstand current	140 A 100 ms 120 A 500 ms 100 A 1 s
Associated fuse rating	10 A gG conforming to IEC 60947-5-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-5-1 600 V certifications CSA 600 V certifications UL
Mounting support	Plate Rail
Connections - terminals	Spring terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: solid - without cable end Spring terminals 1 cable(s) 1...2.5 mm ² - cable stiffness: solid - without cable end Spring terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - without cable end Spring terminals 1 cable(s) 1...2.5 mm ² - cable stiffness: flexible - without cable end
Control circuit voltage limits	0.1...0.25 Uc drop-out 0.7...1.25 Uc operational
Operating time	28...42 ms coil de-energisation and NC closing 57...77 ms coil energisation and NC opening 14...25 ms coil de-energisation and NO opening 65...88 ms coil energisation and NO closing
Mechanical durability	30 Mcycles
Operating rate	180 cyc/mn
Time constant	40 ms
Inrush power in W	2.4 W at 20 °C
Hold-in power consumption in W	2.4 W at 20 °C
Minimum switching voltage	17 V
Minimum switching current	5 mA
Non-overlap time	1.5 ms on de-energisation (between NC and NO contact) 1.5 ms on energisation (between NC and NO contact)
Insulation resistance	> 10 MOhm
Height	99 mm
Width	45 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Depth	93 mm
Product weight	0.58 kg

Environment

Standards	BS 4794 EN 60947-5 IEC 60947-5-1 NF C 63-140 VDE 0660
Product certifications	CSA UL
IP degree of protection	IP2x conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-40...70 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating in temperature
Mechanical robustness	Vibrations control relay closed 4 Gn, 5...300 Hz IEC 60068-2-6 Vibrations control relay open 2 Gn, 5...300 Hz IEC 60068-2-6 Shocks control relay closed 15 Gn for 11 ms IEC 60068-2-27 Shocks control relay open 10 Gn for 11 ms IEC 60068-2-27