



Main

Range of product	Acti 9
Product name	Acti 9 MIN
Device short name	MINs
Product or component type	Silent electronic timer
Product compatibility	Mechanical compatibility with electrical comb busbars
Colour tint	White (RAL 9003)

Complementary

Device application	Building
Load type	230 V AC halogen lamp (2300 W) 230 V AC incandescent lamp (2300 W) 9 fluorescent lamp electronic ballast (7 W) dual mounted fluorescent tube conventional ballast (2300 VA) fluorescent tube electronic ballast (300 VA) non-corrected fluorescent tube conventional ballast (2300 VA) serial-corrected fluorescent tube conventional ballast (2300 VA) 7 fluorescent lamp electronic ballast (11 W) 7 fluorescent lamp electronic ballast (15 W) 7 fluorescent lamp electronic ballast (20 W) 7 fluorescent lamp electronic ballast (23 W) fluocompact lamp conventional ballast (1500 VA) parallel-corrected fluorescent tube conventional ballast (400 VA)
Maximum power consumption in VA	6 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz
Time delay	Adjustable from 0.5 to 20 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals - ≤ 6 mm²
Electrical insulation class	Class II
Width	18 mm

Height	89 mm
Depth	66 mm
Product weight	75 g

Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP20 B

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------