Product datasheet Characteristics

CCT15368

Acti 9 - IC2000 - twilight switch - 2...2000 lux





Commercial status

Discontinued: 31 May 2019

Main

TTT COLOR		
Range of product	Acti 9	
Product name	Acti 9 IC	
Product or component type	Twilight switch	
Device short name	IC2000	
Provided equipment	wall-mounted cell	
Load type	230 V AC halogen lamp: 2300 W 230 V AC incandescent lamp: 2300 W dual mounted fluorescent tube with conventional ballast: 2300 VA dual mounted fluorescent tube with electronic ballast: 300 VA fluocompact lamp with conventional ballast: 1500 VA non-corrected fluorescent tube with conventional ballast: 2300 VA parallel-corrected fluorescent tube with conventional ballast: 400 VA parallel-corrected mercury and sodium vapour lamps: 400 VA serial-corrected fluorescent tube with conventional ballast: 2300 VA 7 x 11 W fluocompact lamp with electronic ballast 7 x 20 W fluocompact lamp with electronic ballast 7 x 23 W fluocompact lamp with electronic ballast 9 x 7 W fluocompact lamp with electronic ballast	
Function available	Cabling test function with a push-button on front face	

Complementary

Complementary		
Device application	Building	
Number of channels	1	
Power consumption in VA	6 VA	- 0 7
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz	t d
Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1	. <u> </u>
Electrical insulation class	Class II	<u>.</u>
Opening distance	< 3 mm	
Status LED	LED (green)threshold reached: LED (red)brightness less than the threshold:	:E
Time delay	>= 60 s on closing >= 60 s on breaking contact	s. la Diriculari

9 mm pitches	5
Light intensity adjustment	22000 lux
Connections - terminals	2 x 2.5 mm² screwless terminals
Height	85 mm
Width	45 mm
Depth	65 mm
Product weight	280 g
Brightness sensing type	Analog wall-mounted cell
Control type	By brightness detection
Market segment	Residential Small commercial
Compatibility code	IC2000

Environment

Ambient air temperature for operation	-2550 °C
IP degree of protection	IP20 B
Standards	EN 60529 EN 60669

Offer Sustainability

Sustainable offer status	Green Premium product	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

Contractual warranty

Warranty	18 months	

CCT15368 is replaced by:





IC CCT15369

Acti 9 IC2000 outdoor (2 - 2000 lux) twilight switch

Qty 1

Reason for Substitution: End of life | Substitution date: 22 October 2019