



Main

Range of product	Acti 9
Product name	Acti 9 IHP
Device short name	IHP
Product or component type	Programmable digital time switch
Device application	Building
Battery type	Lithium
Number of channels	1
Available equipment	Memory key
Language	Italian Portuguese French Spanish Dutch English
Colour tint	White (RAL 9003)

Complementary

Load type	incandescent lamp: ≤ 2000 W halogen lamp: ≤ 2000 W parallel-corrected fluorescent tube with conventional ballast: ≤ 1300 W (140 μ F) fluocompact lamp with electronic ballast: ≤ 300 W dual corrected fluorescent tube with conventional ballast: ≤ 2000 W non-corrected fluorescent tube with conventional ballast: ≤ 2000 W dual mounted fluorescent tube with conventional ballast: ≤ 2000 W 2...8 W LED lamp: ≤ 180 W < 2 W LED lamp: ≤ 55 W
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V AC - 15...10 % at 50/60 Hz
Number of inputs	1 input(s) impulse and maintained
Accuracy	+/- 0.25 s/day 25 °C

Cycle duration	24 hours + 7 days
Maximum number of switchings	84
Minimum interval duration	1 s
Display type	LCD
Battery life	10 year(s)
Backup time	10 years time and program saving
9 mm pitches	2
Width	18 mm
Height	90 mm
Depth	66 mm
Product weight	0.09 kg
Function	Pulse programming, random function, external input for override
Absence for holidays	Yes
Time changeover	Automatic
Updated by	None
Compatibility code	IHP

Environment

Ambient air temperature for operation	-25...55 °C
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------