



Main

Range of product	Acti 9
Product name	Acti 9 ITA
Device short name	ITA
Product or component type	Yearly programmable time switch
Device application	Building
Battery type	Lithium
Number of channels	1
Language	Romanian English Danish German Spanish Italian Swedish French Norwegian Dutch Czech Hungarian Polish Finnish Portuguese
Colour tint	White (RAL 9003)

Complementary

Maximum switching current	16 A - 250 V AC pf = 1 6 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V AC at 50/60 Hz
Accuracy	+/- 0.5 s/day 20 °C
Cycle duration	24 hours + 7 days + year
Maximum number of switchings	300
Minimum interval duration	1 s

Function available	Manual or software programming Cycle programming Time synchronisation via antenna possible External input for override Automatic winter/summer time changeover Pulse programming
Display type	Backlit LCD
Battery life	10 year(s)
Backup time	10 years time and program saving
Type of setting	Absence for holidays function PIN code
Connections - terminals	screw terminals
Mounting support	DIN rail
9 mm pitches	4
Width	35.8 mm
Height	90 mm
Depth	63 mm
Function	Pulse programming
Absence for holidays	Yes
Time changeover	Automatic
Updated by	DCF77 GPS
Compatibility code	ITA
Market segment	Small commercial

Environment

Ambient air temperature for operation	-30...55 °C
IP degree of protection	IP20

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------