
PRODUCT-DETAILS

CMP187-0-BG

SHRINK-KON 300M BLACK



General Information

| | |
|-----------------------|--|
| Extended Product Type | CMP187-0-BG |
| Product ID | 7TCA017300R0076 |
| EAN | 5414363102403 |
| Catalog Description | SHRINK-KON 300M BLACK |
| Long Description | Heat Shrink Tubing, 4.8mm, Black, 300M per bag, Thin Wall, Shrink Ration 2:1, Material - CrossLinked Polyolefin, Item is Silicone, Cadmium and Lead Free |

Ordering

| | |
|-----|---------------|
| EAN | 5414363102403 |
|-----|---------------|

Dimensions

| | |
|--------------------|--------------------|
| Product Net Weight | 5.5 lb 2.494 kg |
|--------------------|--------------------|

Container Information

| | |
|------------------------|-------------------|
| Package Level 2 Units | 1 reel |
| Package Level 2 Width | 15.4 in 391 mm |
| Package Level 2 Height | 6.3 in 160 mm |

| | |
|--------------------------------|-------------------|
| Package Level 2 Depth / Length | 15.4 in 391 mm |
|--------------------------------|-------------------|

Additional Information

| | |
|----------------------------|----------------------------------|
| Brand / Label | Shrink-Kon |
| Color | Black |
| Number of Batteries | 0 |
| Process Temperature Rating | -67 to +275 °F -55 to +135 °C |
| Product Name | PLASTIC CONDUIT |
| Product Type | Thin-Wall Heat Shrinkable Tubing |
| Shrink Ratio | 2:1 |
| Shrink Temperature | 230 °F 110 °C |
| Thickness | Thin |
| UPC | 786210589220 |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-------------|
| Data Sheet, Technical Information | CMP187-0-BG |
| Instructions and Manuals | CMP187-0-BG |

Classifications

| | |
|------------------------------------|------------------------------|
| ETIM 6 | EC000217 - Shrink tubing |
| ETIM 7 | EC000217 - Shrink tubing |
| UNSPSC | 39121723 |
| WEEE Category | Product Not in WEEE Scope |
| IDEA Granular Category Code (IGCC) | 5073 >> Heat shrinkable tube |

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

